

## Scheda di sicurezza

Data di revisione: 3/9/2020, revisione 4

### SEZIONE 1: identificazione della sostanza/miscela e della società/impresa

#### 1.1. Identificatore del prodotto

Identificazione della miscela:

Nome commerciale: ESSELUNGA BAGNO ECOLABEL-RSPO MASS BALAN

Codice commerciale: 001490

Tipo di prodotto ed impiego: Detergente per superfici dure

#### 1.2. Usi identificati pertinenti della sostanza o della miscela e usi sconsigliati

Usi raccomandati:

SU21 Usi di consumo: nuclei familiari/popolazione in generale/consumatori

SU22 Usi professionali

Detergente per superfici dure

Usi sconsigliati:

Tutti gli usi non espressamente indicati sull'etichetta applicata sulla confezione del prodotto

#### 1.3. Informazioni sul fornitore della scheda di dati di sicurezza

Fornitore:

MADEL S.P.A.

Via Evangelista Torricelli n°3 - 48033 Cotignola (RA) -Italy

Tel. +39 0545/908511 (disponibile solo nelle ore d'ufficio lu-ve 08:00-12:30 14:00-18:00)

Fax +39 0545/992259

Persona competente responsabile della scheda di dati di sicurezza:

laboratoriomadel@madel.net

#### 1.4. Numero telefonico di emergenza

MADEL SPA +39 0545 908511 (disponibile solo nelle ore d'ufficio lu-ve 08:00-12:30 14:00-18:00)

CENTRO ANTIVELENI Osp. NIGUARDA Ca' Granda MILANO +39 02 66101029

CENTRO ANTIVELENI Centro Nazionale di Informazione Tossicologica -PAVIA +39 0382 24444

CENTRO ANIVELENI Az. Ospedaliera CAREGGI U.O. Tossicologia Medica-FIRENZE +39 055 7947819

CENTRO ANTIVELENI Policlinico A.GEMELLI -ROMA +39 06 3054343

CENTRO ANTIVELENI Az. Ospedaliera "A. CARDARELLI"-NAPOLI +39 081 7472870

CENTRO ANTIVELENI "Osp. Pediatrico Bambino Gesù" Dip. Emergenza e Accettazione DEA -ROMA +39 06 68593726

CENTRO ANTIVELENI Az. Ospedaliera Università Foggia -FOGGIA 800183459

CENTRO ANTIVELENI Policlinico "Umberto I" -ROMA +39 06 49978000

CENTRO ANTIVELENI Az. Ospedaliera Papa Giovanni XXII -BERGAMO 800883300

### SEZIONE 2: identificazione dei pericoli

#### 2.1. Classificazione della sostanza o della miscela

Criteri Regolamento CE 1272/2008 (CLP):

Il prodotto non è considerato pericoloso in accordo con il Regolamento CE 1272/2008 (CLP).

Effetti fisico-chimici dannosi alla salute umana e all'ambiente:

Nessun altro pericolo

#### 2.2. Elementi dell'etichetta

Il prodotto non è considerato pericoloso in accordo con il Regolamento CE 1272/2008 (CLP).

Pittogrammi di pericolo:

## Scheda di sicurezza

Data di revisione: 3/9/2020, revisione 4

Nessuna  
 Indicazioni di pericolo:  
 Nessuna  
 Consigli di prudenza:  
 Nessuna  
 Disposizioni speciali:  
 Nessuna  
 Dichiarazione degli ingredienti secondo Reg (CE) 648/2004:  
 Inf 5%: tensioattivi anionici, tensioattivi non ionici.  
 Altri componenti: profumo.  
 Disposizioni speciali in base all'Allegato XVII del REACH e successivi adeguamenti:  
 Nessuna

2.3. Altri pericoli  
 Sostanze vPvB: Nessuna - Sostanze PBT: Nessuna  
 Altri pericoli:  
 Nessun altro pericolo

### SEZIONE 3: composizione/informazioni sugli ingredienti

3.1. Sostanze  
 N.A.  
 3.2. Miscele  
 Componenti pericolosi ai sensi del Regolamento CLP e relativa classificazione:

Qtà	Nome	Numero d'identif.	Classificazione
>= 3% - < 5%	Citric acid	CAS: 5949-29-1 EC: 201-069-1 REACH No.: 01-2119457026-42	⚠ 3.3/2 Eye Irrit. 2 H319

(#) REACH N°: Non pertinente (polimero)  
 (\*\*\*) REACH N°: Esonerato secondo REACH articolo 2(7) e allegato V. Ogni materiale di partenza della miscela ionica è registrato, come richiesto.  
 (^) Riferimento ai limiti di concentrazione specifici.  
 (@) Nell'ambito della registrazione REACH, gli enzimi sono definiti come concentrati di enzimi (sulla sostanza secca)

### SEZIONE 4: misure di primo soccorso

4.1. Descrizione delle misure di primo soccorso  
 In caso di contatto con la pelle:  
 Lavare immediatamente con abbondante acqua corrente ed eventualmente sapone le aree del corpo che sono venute a contatto con il prodotto, anche se solo sospette.  
 Consultare un medico se dovesse insorgere irritazione.  
 In caso di contatto con gli occhi:  
 Togliere le eventuali lenti a contatto se è agevole farlo.  
 Lavare immediatamente ed abbondantemente con acqua corrente, a palpebre aperte, per almeno 10 minuti; quindi proteggere gli occhi con garza sterile o un fazzoletto pulito, asciutti. RICORRERE A VISITA MEDICA.  
 Non usare colliri o pomate di alcun genere prima della visita o del consiglio dell'oculista.

## Scheda di sicurezza

Data di revisione: 3/9/2020, revisione 4

Proteggere l'occhio illeso.

In caso di ingestione:

Non provocare assolutamente il vomito. RICORRERE IMMEDIATAMENTE A VISITA MEDICA.

Non dare nulla da mangiare o da bere.

Contattare un Centro Antiveleni (Rif. paragrafo 1)

In caso di inalazione:

Il prodotto non presenta un rischio inalatorio nelle normali condizioni di impiego. Se necessario aerare l'ambiente

**Per una manipolazione prolungata del prodotto puro:**

Aerare l'ambiente. Rimuovere subito il paziente dall'ambiente contaminato e tenerlo a riposo in ambiente ben areato. In caso di malessere consultare un medico.

#### 4.2. Principali sintomi ed effetti, sia acuti che ritardati

In caso di ingestione, contatto cutaneo, contatto oculare:

Nausea, vomito, diarrea.

Sensazione di dolore a carico di faringe, stomaco e addome.

Possibile insufficienza respiratoria nelle vie aeree (specialmente in seguito a episodi di vomito).

Tosse, dispnea.

Congiuntivite

#### 4.3. Indicazione dell'eventuale necessità di consultare immediatamente un medico e di trattamenti speciali

Trattamento:

Trattamento sintomatico.

Contattare un CENTRO ANTIVELENI (Rif. paragrafo 1)

## SEZIONE 5: misure antincendio

#### 5.1. Mezzi di estinzione

Mezzi di estinzione idonei:

Acqua nebulizzata

Biossido di carbonio (CO<sub>2</sub>).

Estinguere gli incendi di grosse dimensioni con acqua nebulizzata o con schiuma resistente all'alcool.

Mezzi di estinzione che non devono essere utilizzati per ragioni di sicurezza:

Getti d'acqua: usare getti d'acqua unicamente per raffreddare le superfici dei contenitori esposti al fuoco.

Nessuno in particolare.

#### 5.2. Pericoli speciali derivanti dalla sostanza o dalla miscela

Evitare di respirare i fumi.

I fumi generati dalla combustione possono essere anche fortemente irritanti per gli occhi, le vie respiratorie e la pelle.

In caso di incendio si possono liberare: Biossido di carbonio (CO<sub>2</sub>) e monossido di carbonio (CO).

#### 5.3. Raccomandazioni per gli addetti all'estinzione degli incendi

Impiegare apparecchiature respiratorie adeguate.

Raccogliere separatamente l'acqua contaminata utilizzata per estinguere l'incendio. Non scaricarla nella rete fognaria.

Se fattibile sotto il profilo della sicurezza, spostare dall'area di immediato pericolo i contenitori non danneggiati.

Consultare le misure protettive esposte al punto 7 e 8.

## Scheda di sicurezza

Data di revisione: 3/9/2020, revisione 4

### SEZIONE 6: misure in caso di rilascio accidentale

- 6.1. Precauzioni personali, dispositivi di protezione e procedure in caso di emergenza  
Non effettuare nessun intervento se questo comporta qualsiasi rischio personale.  
Allontanare il personale non necessario e non protetto.  
Non camminare sul materiale versato.  
Evitare di respirare vapori o nebbie.  
Indossare i dispositivi di protezione individuale.  
Consultare le misure protettive esposte al punto 7 e 8.
- 6.2. Precauzioni ambientali  
Se il prodotto è in forma liquida, impedire che penetri nella rete fognaria.  
Contenere le perdite con terra o sabbia.  
Se il prodotto è defluito in un corso d'acqua, in rete fognaria o ha contaminato il suolo o la vegetazione, avvisare le autorità competenti.  
Trattenere l'acqua di lavaggio contaminata ed eliminarla.
- 6.3. Metodi e materiali per il contenimento e per la bonifica  
Raccogliere il prodotto per il riutilizzo, se possibile, o per l'eliminazione. Eventualmente assorbirlo con materiale inerte.  
Successivamente alla raccolta, lavare con acqua la zona ed i materiali interessati.
- 6.4. Riferimento ad altre sezioni  
Vedi anche paragrafo 8 e 13

### SEZIONE 7: manipolazione e immagazzinamento

- 7.1. Precauzioni per la manipolazione sicura  
Evitare il contatto e l'inalazione dei vapori. Vedere anche il successivo paragrafo 8.  
Si rimanda anche al paragrafo 8 per i dispositivi di protezione raccomandati.  
Raccomandazioni generali sull'igiene del lavoro:  
Durante il lavoro non mangiare né bere.
- 7.2. Condizioni per lo stoccaggio sicuro, comprese eventuali incompatibilità  
Evitare lo stoccaggio a temperature inferiori a 10°C e superiori a 40 °C  
Conservare lontano dalla portata dei bambini.  
Conservare nel contenitore originale ben chiuso.  
Tenere i contenitori in posizione verticale e sicura evitando la possibilità di cadute o urti.  
Tenere lontano da cibi, bevande e mangimi.  
Materie incompatibili:  
Nessuna in particolare.  
Indicazione per i locali:  
Locali adeguatamente areati.
- 7.3. Usi finali particolari  
Seguire le indicazioni riportate sull'etichetta applicata sulla confezione del prodotto.

### SEZIONE 8: controllo dell'esposizione/protezione individuale

- 8.1. Parametri di controllo  
Non sono disponibili limiti di esposizione lavorativa  
Valori limite di esposizione DNEL  
Citric acid - CAS: 5949-29-1

## Scheda di sicurezza

Data di revisione: 3/9/2020, revisione 4

Note: Nessun dato rilevante per tossicità sistemica

Note: Data not provided by the registrant-Rif. ECHA Brief Profile

Valori limite di esposizione PNEC

Citric acid - CAS: 5949-29-1

Bersaglio: Acqua di mare - Valore: 0.044 mg/l

Bersaglio: Sedimenti d'acqua dolce - Valore: 3.46 mg/kg - Note: (Equivalent to 0,752 mg/kg wwt)

Bersaglio: Sedimenti d'acqua dolce - Valore: 34.6 mg/kg - Note: (Equivalent to 7,52 mg/kg wwt)

### 8.2. Controlli dell'esposizione

Protezione degli occhi:

**Per l'utilizzo normale (consumatore finale):**

Non richiesto per l'uso normale. Operare comunque secondo le buone pratiche di lavoro.

**Per una manipolazione prolungata del prodotto puro:**

Utilizzare occhiali protettivi con protezioni laterali (EN 166)

Protezione della pelle:

**Per l'utilizzo normale (consumatore finale):**

Non è richiesta l'adozione di alcuna precauzione speciale per l'uso normale.

**Per una manipolazione prolungata del prodotto puro:**

Utilizzare indumenti o calzature impermeabili.

Scegliere l'indumento protettivo idoneo secondo l'attività e l'esposizione (es: grembiule, stivali, indumenti idonei in accordo con la norma EN14605 in caso di spruzzi).

Protezione delle mani:

**Per l'utilizzo normale (consumatore finale):**

Si consigliano guanti di protezione impermeabili in neoprene, gomma naturale, lattice a seconda di eventuali incompatibilità della persona.

Lo spessore dipende dalle condizioni d'impiego che possono essere variabili.

Si presume che uno spessore di almeno 0,2 mm sia sufficiente per garantire una protezione minima di 1h.

**Per una manipolazione prolungata del prodotto puro:**

Usare guanti protettivi resistenti ai prodotti chimici (EN 374)

(es. nitrile spessore minimo 0,3 mm; tempo di rottura >480 min)

(es. gomma butilica spessore minimo 0,5mm; tempo di rottura >480 min)

In relazione al tempo di contatto utilizzare guanti con IP (Indice di Permeazione) adeguato.

**Indicazioni generali per l'utilizzo dei guanti protettivi:**

Il materiale dei guanti deve essere impermeabile e stabile contro il prodotto/la formulazione.

I guanti devono essere controllati prima di essere usati per accertare l'assenza di difetti o imperfezioni.

Osservare le istruzioni e le informazioni del fabbricante quanto all'impiego, allo stoccaggio, alla cura e sostituzione dei guanti.

I guanti protettivi devono essere immediatamente sostituiti non appena presentano danno o usura.

Rimuovere sempre i guanti senza toccare la superficie esterna del guanto per evitare contaminazioni.

Protezione respiratoria:

Non necessaria per l'utilizzo normale.

**Per una manipolazione prolungata del prodotto puro:**

In caso di superamento del valore di soglia di una o più delle sostanze presenti nel prodotto si consiglia di indossare una maschera con filtro di tipo A-AX il cui limite di utilizzo sarà definito dal fabbricante (EN14387- EN141)

In caso di sviluppo di vapori/aerosoli si consiglia un filtro con potere di ritenzione medio

## Scheda di sicurezza

Data di revisione: 3/9/2020, revisione 4

(Es: EN143 o 149, Tipo P2 o FFP2)

In caso di rischio di esposizione ad elevate concentrazioni di vapori si consiglia un filtro di tipo A (EN141) o una maschera a pieno facciale (EN136) o un respiratore con maschera semifacciale (EN140)

Rischi termici:

Il prodotto non presenta un rischio termico nelle condizioni di stoccaggio ed uso raccomandate (Vedi paragrafo 7).

Controlli dell'esposizione ambientale:

Vedere anche il successivo paragrafo 13

Controlli tecnici idonei:

Locali adeguatamente areati

Vedere anche il precedente paragrafo 7.

### SEZIONE 9: proprietà fisiche e chimiche

#### 9.1. Informazioni sulle proprietà fisiche e chimiche fondamentali

Proprietà	Valore	Metodo:	Note:
Aspetto e colore:	Liquido incolore	Visivo	--
Odore:	Caratteristico	Olfattivo	--
Soglia di odore:	n.d./n.r.	--	Questa proprietà non è pertinente per la sicurezza e la classificazione del prodotto.
pH:	2,1-2,5	M32.00 (t.q. 20°C)	--
Punto di fusione/ congelamento:	<0°C	--	Il prodotto è una soluzione acquosa.
Punto di ebollizione iniziale e intervallo di ebollizione:	>90°C	--	Il prodotto è una soluzione acquosa.
Punto di infiammabilità:	n.d./n.r. ° C	--	Il prodotto è una soluzione acquosa.
Velocità di evaporazione:	n.d./n.r.	--	Questa proprietà non è pertinente per la sicurezza e la classificazione del prodotto.
Infiammabilità solidi/gas:	n.d./n.r.	--	Il prodotto è una soluzione acquosa.
Limite superiore/inferiore d'infiammabilità o esplosione:	n.d./n.r.	--	Il prodotto è una soluzione acquosa
Pressione di vapore:	n.d./n.r.	--	Il prodotto è una soluzione acquosa
Densità dei vapori:	n.d./n.r.	--	Il prodotto è una soluzione acquosa.

## Scheda di sicurezza

Data di revisione: 3/9/2020, revisione 4

Densità relativa:	1.024 +/- 0.005 g/ml	M 43.00 - Densimetro (20°C)	--
Idrosolubilità:	Solubile	--	--
Solubilità in olio:	n.d./n.r.	--	Il prodotto è una soluzione acquosa contenente tensioattivi
Coefficiente di ripartizione (n-ottanolo/acqua):	n.d./n.r.	--	Il prodotto è una soluzione acquosa contenente sostanze tensioattive.
Temperatura di autoaccensione:	n.d./n.r.	--	Il prodotto è una soluzione acquosa.
Temperatura di decomposizione:	n.d./n.r.	--	Questa proprietà non è pertinente per la sicurezza e la classificazione del prodotto.
Viscosità:	n.d./n.r.	--	Il prodotto è una soluzione acquosa.
Proprietà esplosive:	n.d./n.r.	--	Non classificato come esplosivo, non contiene sostanze esplosive secondo reg CLP Art. (14(2))
Proprietà comburenti:	n.d./n.r.	--	Il prodotto non è una sostanza ossidante

### 9.2. Altre informazioni

Proprietà	Valore	Metodo:	Note:
Miscibilità:	n.d./n.r.	--	Questa proprietà non è pertinente per la sicurezza e la classificazione del prodotto.
Liposolubilità:	n.d./n.r.	--	Questa proprietà non è pertinente per la sicurezza e la classificazione del prodotto.
Conducibilità:	n.d./n.r.	--	--
Proprietà caratteristiche dei gruppi di sostanze	n.d./n.r.	--	Il prodotto è una miscela di sostanze.

## SEZIONE 10: stabilità e reattività

10.1. Reattività  
Stabile in condizioni normali

10.2. Stabilità chimica

## Scheda di sicurezza

Data di revisione: 3/9/2020, revisione 4

Il prodotto è stabile nelle condizioni di stoccaggio ed uso raccomandate (si veda paragrafo 7).

- 10.3. Possibilità di reazioni pericolose  
Non sono noti prodotti di decomposizione pericolosi.  
In caso di incendio possono formarsi fumi tossici (COx, NOx).
- 10.4. Condizioni da evitare  
Evitare calore, fiamme libere e altre sorgenti di ignizione.
- 10.5. Materiali incompatibili  
Nessuna in particolare.  
Evitare il contatto con acidi forti.  
Evitare il contatto con sostanze ossidanti.
- 10.6. Prodotti di decomposizione pericolosi  
Non sono noti prodotti di decomposizione pericolosi.  
In caso di incendio possono formarsi fumi tossici (COx, NOx).

### SEZIONE 11: informazioni tossicologiche

- 11.1. Informazioni sugli effetti tossicologici  
Informazioni tossicologiche riguardanti il prodotto:  
N.A.  
Informazioni tossicologiche riguardanti le principali sostanze presenti nel prodotto:  
Citric acid - CAS: 5949-29-1
- a) tossicità acuta:  
Test: LD50 - Via: Orale - Specie: Topo = 5400 mg/kg - Fonte: Rif. ECHA Brief Profile - Note: bw  
Test: LD50 - Via: Pelle - Specie: Ratto = 2000 mg/kg - Fonte: Rif. ECHA Brief Profile - Note: bw
- b) corrosione/irritazione cutanea:  
Test: Non irritante - Via: Pelle - Fonte: Rif. ECHA Brief Profile - Note: No adverse effect observed  
Test: Non irritante - Via: Occhi
- Citric acid - CAS: 5949-29-1  
DL50 orale ratto: >11700 mg/kg  
Contatto con gli occhi: irritante.  
Contatto con la pelle: bruciore sulle ferite.  
Sensibilizzazione: sono possibili sensibilizzazioni allergiche.
- Se non diversamente specificati, i dati richiesti dal Regolamento (UE)2015/830 sotto indicati sono da intendersi N.A.:
- a) tossicità acuta;  
b) corrosione/irritazione cutanea;  
c) lesioni oculari gravi/irritazioni oculari gravi;  
d) sensibilizzazione respiratoria o cutanea;  
e) mutagenicità delle cellule germinali;  
f) cancerogenicità;  
g) tossicità per la riproduzione;  
h) tossicità specifica per organi bersaglio (STOT) — esposizione singola;  
i) tossicità specifica per organi bersaglio (STOT) — esposizione ripetuta;  
j) pericolo in caso di aspirazione.



## Scheda di sicurezza

Data di revisione: 3/9/2020, revisione 4

### SEZIONE 12: informazioni ecologiche

Non sono disponibili dati ecologici sul preparato in quanto tale. Si tenga, quindi, presente la concentrazione delle singole sostanze al fine di valutare gli effetti ecologici derivanti dall'esposizione al preparato.

#### 12.1. Tossicità

Utilizzare secondo le buone pratiche lavorative, evitando di disperdere il prodotto nell'ambiente.

Citric acid - CAS: 5949-29-1

a) Tossicità acquatrica acuta:

Endpoint: LC50 - Specie: Pesci = 440 mg/l - Note: Freshwater fish-Rif. ECHA Brief Profile

#### 12.2. Persistenza e degradabilità

I tensioattivi contenuti in questo formulato sono conformi ai criteri di biodegradabilità stabiliti del Regolamento (CE) n. 648/2004 relativo ai detersivi.

Tutti i dati di supporto sono tenuti a disposizione delle autorità competenti degli Stati Membri e saranno forniti, su loro esplicita richiesta o su richiesta di un produttore del formulato, alle suddette autorità.

Citric acid - CAS: 5949-29-1

Biodegradabilità: Facilmente biodegradabile - Test: In water -screening tests - %: 100% -

Note: Rif. ECHA Brief Profile

#### 12.3. Potenziale di bioaccumulo

Citric acid - CAS: 5949-29-1

Bioaccumulazione: N.D. - Note: No automatically processable data submitted-Rif. ECHA Brief Profile

#### 12.4. Mobilità nel suolo

Citric acid - CAS: 5949-29-1

Mobilità nel suolo: N.D. - Note: No automatically processable data submitted  
-Rif. ECHA Brief Profile

#### 12.5. Risultati della valutazione PBT e vPvB

Sostanze vPvB: Nessuna - Sostanze PBT: Nessuna

#### 12.6. Altri effetti avversi

Non sono noti effetti significativi o pericoli critici.

### SEZIONE 13: considerazioni sullo smaltimento

#### 13.1. Metodi di trattamento dei rifiuti

Recuperare se possibile.

Ove applicabili, si faccia riferimento alle seguenti normative: 91/156/CEE, 91/689/CEE, 94/62/CE e successivi adeguamenti.

Per una gestione dei rifiuti sicura e più favorevole per l'ambiente, si faccia riferimento alle prescrizioni della direttiva 2008/98/CE del Parlamento europeo e del Consiglio.

##### 13.1.1 Prodotto

Il rilascio dei rifiuti in fognature è fortemente sconsigliato. Lo smaltimento di questo prodotto, delle soluzioni e di qualsiasi sottoprodotto deve essere effettuato attenendosi sempre alle indicazioni di legge sulla protezione dell'ambiente e sullo smaltimento dei rifiuti ed ai requisiti di ogni autorità locale pertinente.

Cdicesi rifiuto (European Waste Catalogue):

20 01 29\*: detersivi contenenti sostanze pericolose

## Scheda di sicurezza

Data di revisione: 3/9/2020, revisione 4

### 13.1.2 Imballo

La generazione dei rifiuti dovrebbe essere evitata o minimizzata qualora possibile. Gli imballaggi di scarto devono essere riciclati.

### 13.1.3 Precauzioni particolari

Non disfarsi del prodotto e del recipiente se non con le dovute precauzioni. I contenitori vuoti possono contenere dei residui di prodotto. Evitare la dispersione ed il deflusso di materiale eventualmente sversato ed il contatto con terreno, corsi d'acqua, scarichi e fogne.

## SEZIONE 14: informazioni sul trasporto

### 14.1. Numero ONU

Merce non pericolosa ai sensi delle norme sul trasporto.

### 14.2. Nome di spedizione dell'ONU

N.A.

### 14.3. Classi di pericolo connesso al trasporto

N.A.

### 14.4. Gruppo di imballaggio

N.A.

### 14.5. Pericoli per l'ambiente

ADR-Inquinante ambientale: No

IMDG-Marine pollutant: No

### 14.6. Precauzioni speciali per gli utilizzatori

N.A.

### 14.7. Trasporto di rinfuse secondo l'allegato II di MARPOL ed il codice IBC

N.A.

## SEZIONE 15: informazioni sulla regolamentazione

### 15.1. Disposizioni legislative e regolamentari su salute, sicurezza e ambiente specifiche per la sostanza o la miscela

D.Lgs. 9/4/2008 n. 81

D.M. Lavoro 26/02/2004 (Limiti di esposizione professionali)

Regolamento (CE) n. 1907/2006 (REACH)

Regolamento (CE) n. 1272/2008 (CLP)

Regolamento (CE) n. 790/2009 (ATP 1 CLP) e (UE) n. 758/2013

Regolamento (UE) 2015/830

Regolamento (UE) n. 286/2011 (ATP 2 CLP)

Regolamento (UE) n. 618/2012 (ATP 3 CLP)

Regolamento (UE) n. 487/2013 (ATP 4 CLP)

Regolamento (UE) n. 944/2013 (ATP 5 CLP)

Regolamento (UE) n. 605/2014 (ATP 6 CLP)

Regolamento (UE) n. 2015/1221 (ATP 7 CLP)

Regolamento (UE) n. 2016/918 (ATP 8 CLP)

Regolamento (UE) n. 2016/1179 (ATP 9 CLP)

Regolamento (UE) n. 2017/776 (ATP 10 CLP)

Regolamento (UE) n. 2018/669 (ATP 11 CLP)

Regolamento (UE) n. 2018/1480 (ATP 13 CLP)

Regolamento (UE) n. 2019/521 (ATP 12 CLP)

Restrizioni relative al prodotto o alle sostanze contenute in base all'Allegato XVII del Regolamento (CE) 1907/2006 (REACH) e successivi adeguamenti:

Restrizioni relative al prodotto:

## Scheda di sicurezza

Data di revisione: 3/9/2020, revisione 4

Nessuna restrizione.

Restrizioni relative alle sostanze contenute:

Nessuna restrizione.

Ove applicabili, si faccia riferimento alle seguenti normative:

Circolari ministeriali 46 e 61 (Ammine aromatiche).

Direttiva 2012/18/EU (Seveso III)

Regolamento 648/2004/CE (Detergenti).

D.L. 3/4/2006 n. 152 Norme in materia ambientale

Dir. 2004/42/CE (Direttiva COV)

Disposizioni relative alla direttiva EU 2012/18 (Seveso III):

Categoria Seveso III in accordo all'Allegato 1, parte 1

Nessuno

15.2. Valutazione della sicurezza chimica

Una valutazione della sicurezza chimica non è stata effettuata sulla miscela ma sono disponibili i dati sulle sostanze pericolose in essa contenuti.

### SEZIONE 16: altre informazioni

Testo delle frasi utilizzate nel paragrafo 3:

H319 Provoca grave irritazione oculare.

Classe e categoria di pericolo	Codice	Descrizione
Eye Irrit. 2	3.3/2	Irritazione oculare, Categoria 2

Paragrafi modificati rispetto alla precedente revisione:

SEZIONE 2: identificazione dei pericoli

SEZIONE 15: informazioni sulla regolamentazione

Principali fonti bibliografiche:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

CCNL - Allegato 1

Istituto Superiore di Sanità - Inventario Nazionale Sostanze Chimiche

Procedura di classificazione:

Questo documento e' stato redatto da un tecnico competente in materia di SDS e che ha ricevuto formazione adeguata.

Le informazioni ivi contenute si basano sulle nostre conoscenze alla data sopra riportata. Sono riferite unicamente al prodotto indicato e non costituiscono garanzia di particolari qualità.

La classificazione della miscela è generalmente basata sul metodo di calcolo utilizzando i dati relativi alle sostanze, come richiesto dal Regolamento (EC) N° 1272/2008.

Nel caso siano disponibili dati relativi alla miscela o principi ponte o dati probanti che intervengano sulla classificazione finale della stessa, questi sono indicati nelle sezioni pertinenti della Scheda Dati di Sicurezza (sezione 2).

Consultare la sezione 9 per le caratteristiche chimiche e fisiche, la sezione 11 per le

## Scheda di sicurezza

Data di revisione: 3/9/2020, revisione 4

informazioni tossicologiche e la sezione 12 per le informazioni ecologiche.  
L'utilizzatore è tenuto ad assicurarsi della idoneità e completezza di tali informazioni in relazione all'utilizzo specifico che ne deve fare.

Questa scheda annulla e sostituisce ogni edizione precedente.

### Abbreviazioni ed acronimi

AISE:	Associazione Internazionale per Saponi, detergenti e Prodotti per Manutenzione
DetNet:	Network dell'Industria della Detergenza per la classificazione CLP sviluppato da AISE
TiV:	Test in Vitro
ADR:	Accordo europeo relativo al trasporto internazionale stradale di merci pericolose.
CAS:	Chemical Abstracts Service (divisione della American Chemical Society).
CLP:	Classificazione, Etichettatura, Imballaggio.
DNEL:	Livello derivato senza effetto.
EINECS:	Inventario europeo delle sostanze chimiche europee esistenti in commercio.
GefStoffVO:	Ordinanza sulle sostanze pericolose in Germania.
GHS:	Sistema globale armonizzato di classificazione e di etichettatura dei prodotti chimici.
IATA:	Associazione per il trasporto aereo internazionale.
IATA-DGR:	Regolamento sulle merci pericolose della "Associazione per il trasporto aereo internazionale" (IATA).
ICAO:	Organizzazione internazionale per l'aviazione civile.
ICAO-TI:	Istruzioni tecniche della "Organizzazione internazionale per l'aviazione civile" (ICAO).
IMDG:	Codice marittimo internazionale per le merci pericolose.
INCI:	Nomenclatura internazionale degli ingredienti cosmetici.
KSt:	Coefficiente d'esplosione.
LC50:	Concentrazione letale per il 50 per cento della popolazione di test.
LD50:	Dose letale per il 50 per cento della popolazione di test.
PNEC:	Concentrazione prevista senza effetto.
RID:	Regolamento riguardante il trasporto internazionale di merci pericolose per via ferroviaria.
STA:	Stima della tossicità acuta
STAmix:	Stima della tossicità acuta (Miscela)
STEL:	Limite d'esposizione a corto termine.
STOT:	Tossicità organo-specifica.
TLV:	Valore limite di soglia.
TWA:	Media ponderata nel tempo
WGK:	Classe di pericolo per le acque (Germania).
N.A./N.D.:	Not Available-Non disponibile-Nicht Verfügbar
N.R.:	Non rilevante-Nicht Relevant



# Citric acid

Revision date: 02 Dec 2013

**Annex to extended safety data sheet (eSDS)****Exposure scenario**

Substance / User identity	
Registration number(s)	01-2119457026-42-xxxx
Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario Processes and activities covered by the exposure scenario
	1、 Production of citric acid PROC 1, PROC 2, PROC 3, PROC 4, PROC 8b, SU 3,SU 8,
2	Operational conditions and risk management measures
	Duration an frequency of use
	Worker All applicable PROCs
	>4h
	Physical form of substance:
	Solid.
	Concentration of substance in preparation or article
	90%
	Other relevant operational conditions of use
	No measured data are available for releases of citric acid to air and waste water for the generic production site. Releases are therefore estimated on the basis of other information. Releases to air: Due to the very low vapour pressure of the key intermediates and of citric acid itself, losses to air are considered to be zero. Releases to waste water: The key production stage is the precipitation of calcium citrate. This substance is of low solubility, although a small quantity of citric acid could remain dissolved, a fraction of 0.0001, or 2.86 kg/d over 350 days. There could be losses during handling and packaging processes, but when around 30 tonnes per day are handled these processes are highly automated. It can be anticipated that occasional spillages can occur due to small levels of leakage, amounting to at most 1 kg per day passing to aqueous waste. The total passing to aqueous waste water is 3.86 kg/d.
Risk management measures:	
2.1	Control of worker exposure
	Operational conditions related to respiration and skin contact
	<b>Information type</b>
	<b>Data field</b>
	<b>Explanation</b>
	Respiration volume under conditions of use
	10 m <sup>3</sup> /d
	Default for workers, light activity
	Area of skin contact with the substance under conditions of use
	240 cm <sup>2</sup>
	480 cm <sup>2</sup>
	ECETOC TRA default: PROC 1: palm of one hand PROC 2: palms of both hands



# Citric acid

Revision date: 02 Dec 2013

		240 cm <sup>2</sup>	PROC 3: palm of one hand	
		480 cm <sup>2</sup>	PROC4: palms of both hands	
		480 cm <sup>2</sup>	PROC8b: palms of both hands	
	Body weight	70 kg	Default	
Technical fate of substance and losses from process/use to waste, waste water and air	<b>Information type</b>	<b>Data field</b>	<b>Explanation</b>	
	Fraction of applied amount lost from process/use to waste gas	0 kg/kg	See text	
	Fraction of applied amount lost from process/use to waste water	0.0001 kg/kg	See text	
Engineering controls:				
Personal protective equipment (PPE)	<b>Information type</b>	<b>Data field</b>	<b>Explanation</b>	
	Containment plus good work practice required	Yes		
	Local exhaust ventilation required plus good work practise	Yes	Typical practice of chemical industry. Not applicable for PROC1.	
	Skin protection	Protective gloves		
	Eye protection	Safety glasses		
	Respiratory protection	Dust mask. In case of open handling of larger quantities or accidental release:  particle mask or respirator with independent air supply		
	Clothing	Working clothing worn.		



# Citric acid

Revision date: 02 Dec 2013

Risk management measures related to environmental emissions from industrial sites	Information type	Data field	Explanation
	Onsite pre-treatment of waste water	Yes	Neutralisation
	Resulting fraction of initially applied amount in waste water released from site to the external sewage system		On-site biological waste treatment is expected to remove a high proportion of citric acid, as the substance is highly biodegradable.
	Air emission abatement	No measured data	
	Resulting fraction of applied amount in waste gas released to environment	No measured data	
	Onsite waste treatment	No measured data	Secondary biological treatment
	Fraction of initially applied amount sent to external waste treatment. This is the sum of direct losses from processes to waste, and the residues from onsite waste water and waste gas treatment.	No measured data	
	Municipal or other type of external waste water treatment	None	None
	Effluent (of the waste water treatment plant) discharge rate	1 x 10 <sup>7</sup> l/d	Default for a large industrial site
	Recovery of sludge for agriculture or horticulture	Yes	Dried sludge may be sold as an approved agricultural fertiliser
Frequency and duration of use			

# Citric acid

Revision date: 02 Dec 2013

		Information type	Data field	Explanation			
Use per site Duration of emission Waste water flow Dilution factor		Used amount of substance per day	30 tonnes				
		Duration of exposure per day at workplace [for one worker]	>4 hours (all PROCs)	REACH default used as a w exposure times may be s			
		Frequency of exposure at workplace [for one worker]	Once per day				
		Annual amount used per site	10,000 tonnes				
		Emission days per site	350				
		<b>Information on estimated exposure and Downstream-user guidance</b>					
3	Exposure estimation and reference to its source:						
	Dermal exposure estimates (based on ECETOC TRA model)	<b>Process category</b>	<b>Description</b>	<b>LEV present?</b>	<b>Predicted exposure (<math>\mu\text{g}/\text{cm}^2/\text{day}</math>)</b>	<b>Exposed skin surface area (<math>\text{cm}^2</math>)</b>	<b>Dermal exposure (<math>\text{mg}/\text{kg}/\text{day}</math>)<sup>a</sup></b>
		PROC1	Use in closed process, no likelihood of exposure	Nob	100	240	0.3
		PROC2	Use in closed, continuous process with occasional controlled exposure (e.g. sampling)	Yes	20	480	0.14
		PROC3	Use in closed batch process (synthesis or formulation)	Yes	10	240	0.03
		PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises	Yes	100	480	0.69
		PROC8b	Transfer from/to large vessels	Yes	100	480	0.69





# Citric acid

Revision date: 02 Dec 2013

		(dedicated)				
	<p>a) Calculated assuming a default bodyweight of 70 kg for worker.  b) In the ECETOC TRA model, LEV is not considered relevant for PROC1.</p>					
Inhalation exposure estimates (based on ECETOC TRA model)	<b>Process category</b>	<b>Description</b>	<b>LEV present?</b>	<b>Predicted exposure (ppm)</b>	<b>Predicted exposure (mg/m<sup>3</sup>)<sup>c</sup></b>	<b>Inhalation exposure (mg/kg/day)<sup>d</sup></b>
	PROC1	Use in closed process, no likelihood of exposure	No <sup>b</sup>	0.001	0.01	0.001
	PROC2	Use in closed, continuous process with occasional controlled exposure (e.g. sampling)	Yes	0.01	0.1	0.01
	PROC3	Use in closed batch process (synthesis or formulation)	Yes	0.01	0.1	0.01
	PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises	Yes	0.31	2.5	0.36
	PROC8b	Transfer from/to large vessels(dedicated)	Yes	0.16	1.25	0.18
	<p>b) In the ECETOC TRA model, LEV is not considered relevant for PROC1.  c) Results are calculated as mg/m<sup>3</sup> for solids and ppm for non-solids  d) Calculated assuming a default bodyweight of 70 kg for workers and a default respiratory volume of 10 m<sup>3</sup>, light activity, for an 8 hour work shift</p>					



# Citric acid

Revision date: 02 Dec 2013

	Summary of long-term exposure concentration to workers	<b>Routes of exposure</b>	<b>Concentrations</b>	<b>Justification</b>																					
		Dermal local exposure (in µg/cm <sup>2</sup> )	0.6	ECETOC TRA prediction for PROC8b, multiplied by an uptake factor of 0.006.																					
		Dermal systemic exposure (in mg/kg bw/d)	0.004	ECETOC TRA prediction for PROC8b, multiplied by an uptake factor of 0.006.																					
		Inhalation exposure (in mg/m <sup>3</sup> )/8h workday	2.5	ECETOC TRA prediction for PROC8b																					
		Inhalation exposure (in mg/kg/d)/8h workday	0.36	ECETOC TRA prediction for PROC8b																					
4	Environmental releases	<p>Predicted environmental release estimates have been used for releases during production. No measured data are available for the concentration of citric acid in any environmental compartment. The releases have been estimated using the exposure scenario for production (section 9.1.1.2 and 9.1.1.6) and Predicted Environmental Concentrations have been determined using EUSES 2.1.1. The EUSES program implements the environmental exposure models described in REACH Technical Guidance Chapter R16. Default model parameters have been used unless stated below.</p> <p>The basis of local and regional production tonnages is to consider the sizes of the largest sites in the EU relative to the total tonnage as follows:            Production volume in EU: 100 000 tonnes            Regional tonnage: 10 000 tonnes            Fraction of main local source: 1            Local tonnage: 29 tonnes per day            Number of days: 350</p> <p>The contribution of local releases to the regional concentration has been considered using the appropriate calculation in EUSES 2.1.1.</p>																							
	Predicted environmental release																								
	Summary of Predicted Exposure Concentrations	<table border="1"> <thead> <tr> <th></th> <th>PEC</th> <th>unit</th> </tr> </thead> <tbody> <tr> <td colspan="3"><b>AIR</b></td> </tr> <tr> <td>Annual average local PEC in air (total)</td> <td>3.50 x 10<sup>-16</sup></td> <td>[mg m<sup>-3</sup>]</td> </tr> <tr> <td colspan="3"><b>WATER, SEDIMENT</b></td> </tr> <tr> <td>Local PEC in surface water during emission episode (dissolved)</td> <td>0.0153</td> <td>[mg l<sup>-1</sup>]</td> </tr> <tr> <td>Annual average local PEC in surface water (dissolved)</td> <td>0.0153</td> <td>[mg l<sup>-1</sup>]</td> </tr> <tr> <td>Local PEC in fresh-water sediment during emission episode</td> <td>0.261</td> <td>[mg kg wwt<sup>-1</sup>]</td> </tr> </tbody> </table>				PEC	unit	<b>AIR</b>			Annual average local PEC in air (total)	3.50 x 10 <sup>-16</sup>	[mg m <sup>-3</sup> ]	<b>WATER, SEDIMENT</b>			Local PEC in surface water during emission episode (dissolved)	0.0153	[mg l <sup>-1</sup> ]	Annual average local PEC in surface water (dissolved)	0.0153	[mg l <sup>-1</sup> ]	Local PEC in fresh-water sediment during emission episode	0.261	[mg kg wwt <sup>-1</sup> ]
	PEC	unit																							
<b>AIR</b>																									
Annual average local PEC in air (total)	3.50 x 10 <sup>-16</sup>	[mg m <sup>-3</sup> ]																							
<b>WATER, SEDIMENT</b>																									
Local PEC in surface water during emission episode (dissolved)	0.0153	[mg l <sup>-1</sup> ]																							
Annual average local PEC in surface water (dissolved)	0.0153	[mg l <sup>-1</sup> ]																							
Local PEC in fresh-water sediment during emission episode	0.261	[mg kg wwt <sup>-1</sup> ]																							



# Citric acid

Revision date: 02 Dec 2013

	Local PEC in seawater during emission episode (dissolved)	$1.80 \times 10^{-3}$	[mg l <sup>-1</sup> ]
	Annual average local PEC in seawater (dissolved)	$1.78 \times 10^{-3}$	[mg l <sup>-1</sup> ]
	Local PEC in marine sediment during emission episode	0.0307	[mg kg wwt <sup>-1</sup> ]
	SOIL, GROUNDWATER		
	Local PEC in agric. soil (total) averaged over 30 days	0.0227	[mg kg wwt <sup>-1</sup> ]
	Local PEC in agric. soil (total) averaged over 180 days	$7.43 \times 10^{-3}$	[mg kg wwt <sup>-1</sup> ]
	Local PEC in grassland (total) averaged over 180 days	$2.97 \times 10^{-3}$	[mg kg wwt <sup>-1</sup> ]
	Local PEC in pore water of agricultural soil	$1.12 \times 10^{-4}$	[mg l <sup>-1</sup> ]
	Local PEC in pore water of grassland	$4.48 \times 10^{-5}$	[mg l <sup>-1</sup> ]
	Local PEC in groundwater under agricultural soil	$1.12 \times 10^{-4}$	[mg l <sup>-1</sup> ]



## Citric acid

Revision date: 02 Dec 2013

Substance / User identity				
	Registration number(s)	01-2119457026-42-xxxx		
	Substance identity	CAS#77-92-9; EC#201-069-1		
1	Short title of the exposure scenario	2. Use of citric acid as a chemical intermediate		
	Processes and activities covered by the exposure scenario	SU3 (Industrial uses), SU8, SU9, PROC 1, PROC 2, PROC 3, PROC 4, PROC 8b,		
2	Operational conditions and risk management measures			
	Duration an frequency of use			
	Worker All applicable PROCs	>4h		
	Physical form of substance:	solid		
	Concentration of substance in preparation or article			
Other relevant operational conditions of use				
Risk management measures:				
2.1	Control of worker exposure			
	Containment and local exhaust ventilation	<b>Information type</b>	<b>Data field</b>	<b>Explanation</b>
		Containment plus good work practice required	Yes	
		Local exhaust ventilation required plus good work practise	Yes	Typical practice of chemical industry. Not applicable for PROC1.
	Personal protective equipment (PPE)	<b>Information type</b>	<b>Data field</b>	<b>Explanation</b>
		Skin protection	Protective gloves	
		Eye protection	Safety glasses	
Respiratory protection		Dust mask. In case of open handling of larger quantities or accidental release: particle mask or respirator with independent air supply		
Clothing	Working clothing worn.			



# Citric acid

Revision date: 02 Dec 2013

	Risk management measures related to environmental emissions from industrial sites:	<b>Information type</b>	<b>Data field</b>	<b>Explanation</b>	
		Onsite pre-treatment of waste water	Yes	Neutralisation	
		Resulting fraction of initially applied amount in waste water released from site to the external sewage system		On-site biological waste treatment is expected to remove a high proportion of citric acid, as the substance is highly biodegradable.	
		Air emission abatement	No measured data		
		Resulting fraction of applied amount in waste gas released to environment	No measured data		
		Onsite waste treatment	No measured data	Secondary biological treatment	
		Fraction of initially applied amount sent to external waste treatment. This is the sum of direct losses from processes to waste, and the residues from onsite waste water and waste gas treatment.	No measured data		
		Municipal or other type of external waste water treatment	None	None	
		Effluent (of the waste water treatment plant) discharge rate	1x 10 <sup>7</sup> l/d	Default for a large industrial site	
		Recovery of sludge for agriculture or horticulture	Yes	Dried sludge may be sold as an approved agricultural fertiliser	
2.2	Control of environmental exposure				
	Frequency and duration of use				
	Duration, frequency and amount	<b>Information type</b>	<b>Data field</b>	<b>Explanation</b>	

# Citric acid

Revision date: 02 Dec 2013

	Used amount of substance per day	10,000 kg/d	Generic information	
	Duration of exposure per day at workplace [for one worker]	>4 hours (all PROCs)	REACH default used as a worst case; actually exposure times may be significantly less	
	Frequency of exposure at workplace [for one worker]	Once per day	In situations where the duration of exposure is lower, frequency of exposure may be higher	
	Annual amount used per site	3,000 tpa	Generic information	
	Emission days per site	300 d/y	REACH default number of days for high volumes	
Other operational conditions of use				
	Releases to air	Due to the very low vapour pressure of the key intermediates and of citric acid itself, losses to air are considered to be zero.		
	Releases to water	The REACH ERC 6A (Industrial use of intermediate) release default estimates to waste water is 2%.		
	Technical conditions and measures at process level (source) to prevent release	No specific measures are considered		
	Technical onsite conditions and measures to reduce or limit discharges, air emissions	<p>The default TGD (TGD ESD part IV) release rate from processing of synthetic intermediate is 0.7% by weight for a wet process and 0% for a dry (water-free) process. Processing of citric acid is a wet-process. On-site waste water treatment at the plant (e.g. activated carbon, precipitation and so on) is already included in the emission factors.</p> <p>The default loss of 70 kg/d (EU TGD 0.7% default) from the processing of 30 t/d of citric acid is not considered to be realistic. Realistic losses to waste water from the processing of citric acid at a typical industrial site are expected to come from:</p> <ul style="list-style-type: none"> <li>• Substance washout from ventilation systems</li> <li>• Minor routine spillages</li> <li>• Occasional equipment loss/leakages</li> </ul> <p>Given that a solid is precipitated efficiently it is considered that 7 kg/d is a more realistic estimate.</p> <p>Citric acid is highly degradable and on-site waste water treatment is expected to mean that little of the substance is released to the wider environment.</p> <p>It can be assumed that this process will be taking place at a large industrial site with waste water passing to a larger-than-default WWTP with a flow rate of 10,000 m<sup>3</sup>/day.</p>		
	Technical fate of substance and losses from process/use to waste, waste	<b>Information type</b>	<b>Data field</b>	<b>Explanation</b>

# Citric acid

Revision date: 02 Dec 2013

	water and air	Fraction of applied amount lost from process/use to waste gas	0 kg/kg	See text				
		Fraction of applied amount lost from process/use to waste water	0.007 kg/kg	See text				
Information on estimated exposure and Downstream-user guidance								
3	Exposure estimation and reference to its source:							
	Dermal	Process category	Description	Dermal exposure?	Predicted exposure ( $\mu\text{g}/\text{cm}^2/\text{day}$ )	Exposed skin surface area ( $\text{cm}^2$ )	Dermal exposure ( $\text{mg}/\text{kg}/\text{day}$ ) <sup>a</sup>	
		PROC1	Use in closed process, no likelihood of exposure	Yes	100	240	0.3	
		PROC2	Use in closed, continuous process with occasional controlled exposure	Yes	20	480	0.14	
		PROC3	Use in closed batch process (synthesis or formulation)	Yes	10	240	0.03	
		PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises	Yes	100	480	0.69	
		PROC8b	Transfer from/to large vessels (dedicated)	Yes	100	480	0.69	
	a) Calculated assuming a default bodyweight of 70 kg for worker b) In the ECETOC TRA model, LEV is not considered relevant for PROC1.							

# Citric acid

Revision date: 02 Dec 2013

Inhalation	Process category	Description	LEV present?	Predicted exposure (ppm)	Predicted exposure (mg/m <sup>3</sup> ) <sup>c</sup>	Inhalation Exposure (mg/kg/day) <sup>d</sup>
	PROC1	Use in closed process, no likelihood of exposure	No <sup>b</sup>	0.001	0.01	0.001
	PROC2	Use in closed, continuous process with occasional controlled exposure	Yes	0.01	0.1	0.01
	PROC3	Use in closed batch process (synthesis or formulation)	Yes	0.01	0.1	0.01
	PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises	Yes	0.31	2.5	0.36
	PROC8b	Transfer from/to large vessels (dedicated)	Yes	0.16	1.25	0.18
<p>b) In the ECETOC TRA model, LEV is not considered relevant for PROC1.  c) Results are calculated as mg/m<sup>3</sup> for solids and ppm for non-solids  d) Calculated assuming a default bodyweight of 70 kg for workers and a default respiratory volume of 10 m<sup>3</sup>, light activity, for an 8 hour work shift</p>						
long-term exposure concentration to workers	Routes of exposure	Concentrations	Justification			
	Dermal local exposure (in µg/cm <sup>2</sup> )	0.6	ECETOC TRA prediction for PROC8b, multiplied by an uptake factor of 0.006.			
	Dermal systemic exposure (in mg/kg bw/d)	0.004	ECETOC TRA prediction for PROC8b, multiplied by an uptake factor of 0.006.			
	Inhalation exposure (in mg/m <sup>3</sup> )/8h workday	2.5	ECETOC TRA prediction for PROC8b			
	Inhalation exposure (in mg/kg/d)/8h workday	0.36	ECETOC TRA prediction for PROC8b			



**Citric acid**

Revision date: 02 Dec 2013

Predicted Environmental Concentrations	PEC	unit
	AIR	
Annual average local PEC in air (total)	5.45 x 10 <sup>-16</sup>	[mg m <sup>-3</sup> ]
WATER, SEDIMENT		
Local PEC in surface water during emission episode (dissolved)	0.0154	[mg l <sup>-1</sup> ]
Annual average local PEC in surface water (dissolved)	0.0154	[mg l <sup>-1</sup> ]
Local PEC in fresh-water sediment during emission episode	0.263	[mg kg wwt <sup>-1</sup> ]
Local PEC in seawater during emission episode (dissolved)	0.0084	[mg l <sup>-1</sup> ]
Annual average local PEC in seawater (dissolved)	0.00716	[mg l <sup>-1</sup> ]
Local PEC in marine sediment during emission episode	0.144	[mg kg wwt <sup>-1</sup> ]
SOIL, GROUNDWATER		
Local PEC in agric. soil (total) averaged over 30 days	0.0411	[mg kg wwt <sup>-1</sup> ]
Local PEC in agric. soil (total) averaged over 180 days	0.0135	[mg kg wwt <sup>-1</sup> ]
Local PEC in grassland (total) averaged over 180 days	0.00539	[mg kg wwt <sup>-1</sup> ]
Local PEC in pore water of agricultural soil	0.000203	[mg l <sup>-1</sup> ]
Local PEC in pore water of grassland	0.0000813	[mg l <sup>-1</sup> ]
Local PEC in groundwater under agricultural soil	0.000203	[mg l <sup>-1</sup> ]



# Citric acid

Revision date: 02 Dec 2013

Substance / User identity				
Registration number(s)	01-2119457026-42-xxxx			
Substance identity	CAS#77-92-9; EC#201-069-1			
1	Short title of the exposure scenario	3、 Formulation of citric acid into preparations		
	Processes and activities covered by the exposure scenario	SU3, 10, SU5, SU13, 20 PROC2, PROC3, PROC4, PROC5, PROC7, PROC8a, PROC8b, PROC9, PROC13, PROC14, PROC15, PROC19		
2	Operational conditions and risk management measures			
	Duration an frequency of use			
	Worker All applicable PROCs	>4h		
	Physical form of substance:	solid		
	Concentration of substance in preparation or article			
	Other relevant operational conditions of use	The citrates used in the formulation of products are generally solids which may be mixed with other solids or dissolved in aqueous solution. There is some potential for airborne release of citric acid (or citrate) particulates on charging (transfer, dosing) to the process equipment used, especially if containment is not good. However, the most likely release will be to waste water via clean out or spillage. Taking the HERA figure of approx. 100 000 tpa [HERA, 2005] for total use of citrates in detergents, and realistic values of 10% formulated in a single region, and 60% of that at a single location, gives a volume of 6,000 tpa citrates formulated at a single location. For this generic site, the daily loss rate to waste water is $6000 \text{ t} \times 1000 \text{ kg/t} \times 0.0009 / 300 \text{ d} = 18 \text{ kg/d}$ . The tonnage to be covered is now 150 000 tpa, but the site size is retained. The loss rate is considered to be a reasonable worst case for a large site. At smaller formulation sites the amount handled per day would be lower and the controls could be less, but overall rates per day would be similar.		
Risk management measures:				
2.1	Control of worker exposure			
	Containment and local exhaust ventilation	Information type	Data field	Explanation
		Containment plus good work practice required	Yes	General good hygiene and housekeeping
		Local exhaust ventilation required plus good work practice.	Yes	Typical practice of chemical industry.
	Personal protective equipment (PPE)	Information type	Data field	Explanation
		Skin protection	Protective gloves	
		Eye protection	Safety glasses	
		Clothing	Working clothing worn.	
	Risk management measures related to environmental emissions from industrial sites:	Information type	Data field	Explanation
		Onsite pre-treatment of waste water	Yes	Removal of solids in settling tanks
Resulting fraction of initially applied amount		No measured data		



# Citric acid

Revision date: 02 Dec 2013

		in waste water released from site to the external sewage system		
		Air emission abatement	No measured data	
		Resulting fraction of applied amount in waste gas released to environment	No measured data	See text
		Onsite waste treatment	No	Worst-case assumption as no specific information available.
		Fraction of initially applied amount sent to external waste treatment. This is the sum of direct losses from processes to waste, and the residues from onsite waste water and waste gas treatment.	No measured data	
		Municipal or other type of external waste water treatment	Yes	Typical practise in the chemical industry
		Effluent (of the waste water treatment plant) discharge rate	1 * 10 <sup>7</sup> L/d	Default for a large industrial site.
		Recovery of sludge for agriculture or horticulture	Yes	Worst-case assumption as no specific information available.
2.2	Control of environmental exposure			
	Frequency and duration of use			
	Duration, frequency and amount	Information type	Data field	Explanation
		Used amount of substance per day	6000 tonnes	
		Duration of exposure per day at workplace [for one worker]	>4 hours (all PROCs)	For some applications/setting exposure times may be significantly less
Frequency of exposure at workplace [for one worker]		Once per day	For some applications/settings with shorter duration exposures, multiple exposures may occur in	



# Citric acid

Revision date: 02 Dec 2013

						a single day		
		Annual amount used per site	20 tonnes					
		Emission days per site	300 days					
Information on estimated exposure and Downstream-user guidance								
3	Exposure estimation and reference to its source:							
	Occupational exposure:							
	Dermal							
		Process category	Description	Dermal exposure?	Predicted exposure ( $\mu\text{g}/\text{cm}^2/\text{day}$ )	Exposed skin surface area ( $\text{cm}^2$ )	Dermal exposure ( $\text{mg}/\text{kg}/\text{day}$ ) <sup>a</sup>	
		PROC1	Use in closed process, no likelihood of exposure	Yes	100	240	0.3	
		PROC2	Use in closed, continuous process with occasional controlled exposure (e.g. sampling)	Yes	20	480	0.14	
		PROC3	Use in closed batch process (synthesis or formulation)	Yes	10	240	0.034	
		PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises	Yes	100	480	0.69	
		PROC5	Mixing or blending in batch processes (multistage and/or significant contact)	Yes	200	480	1.37	
		PROC7	Industrial spraying	Yes	200	1500	4.29	
		PROC8a	Transfer from/to large vessels (non-dedicated).	Yes	100	960	1.37	
	PROC8b	Transfer from/to large vessels (dedicated)	Yes	100	480	0.69		
	PROC9	Transfer to small containers	Yes	100	480	0.69		
	PROC13	Treatment of articles by dipping and pouring	Yes	100	480	0.69		

# Citric acid

Revision date: 02 Dec 2013

		PROC14	Production of preparations or articles by tableting, compression, extrusion, pelletisation	Yes	50	480	0.34	
		PROC15	Use of laboratory reagents in small scale laboratories	Yes	10	240	0.034	
		PROC19	Hand-mixing with intimate contact (only PPE available)	Yes	500	1980	14.1	
	Inhalation	Process category	Description	LEV present ?	Predicted exposure (ppm)	Predicted exposure (mg/m <sup>3</sup> ) <sup>c</sup>	Inhalation Exposure (mg/kg/day) <sup>d</sup>	
		PROC1	Use in closed process, no likelihood of exposure	No <sup>b</sup>	0.0013	0.01	0.0014	
		PROC2	Use in closed, continuous process with occasional controlled exposure (e.g. sampling)	Yes	0.0125	0.1	0.014	
		PROC3	Use in closed batch process (synthesis or formulation)	Yes	0.0125	0.1	0.014	
		PROC4	Use in batch and other process (synthesis) where opportunity for exposure arises	Yes	0.31	2.5	0.36	
		PROC5	Mixing or blending in batch processes (multistage and/or significant contact)	Yes	0.31	2.5	0.36	
		PROC7	Industrial spraying	Yes	1.25	10	1.43	
		PROC8a	Transfer from/to large vessels (non-dedicated)	Yes	0.63	5	0.71	
		PROC8b	Transfer from/to large vessels (dedicated)	Yes	0.31	2.5	0.36	
		PROC9	Transfer to small	Yes	0.25	2	0.29	



# Citric acid

Revision date: 02 Dec 2013

		containers						
		PROC13	Treatment of articles by dipping and pouring	Yes	0.0013	0.01	0.0014	
		PROC14	Production of preparations or articles by tableting, compression, extrusion, pelletisation	Yes	0.13	1	0.14	
		PROC15	Use of laboratory reagents in small scale laboratories	Yes	0.063	0.5	0.071	
		PROC19	Hand-mixing with intimate contact (only PPE available)	Yes	0.0063	0.05	0.0071	
		b) Results are calculated as mg/m3 for solids and ppm for non-solids c) Calculated assuming a default bodyweight of 70 kg for workers and a default respiratory volume of 10 m3, light activity, for an 8 hour work shift						
	long-term exposure concentration to workers	Routes of exposure	Concentration	Justification				
		Dermal local exposure (in µg/cm2)	3	ECETOC TRA prediction for PROC19, multiplied by an uptake factor of 0.006.				
		Dermal systemic exposure (in mg/kg bw/d)	0.08	ECETOC TRA prediction for PROC19, multiplied by an uptake factor of 0.006.				
		Inhalation exposure (in mg/m3)/8h workday	10	ECETOC TRA prediction for PROC7				
		Inhalation exposure (in mg/kg/d)/8h workday	1.43	ECETOC TRA prediction for PROC7				
	Predicted Exposure Concentrations ( PEC )		<b>PEC</b>	<b>unit</b>				
		<b>AIR</b>						
		Annual average local PEC in air (total)	1.4 x 10 <sup>-15</sup>			[mg.m <sup>-3</sup> ]		
		<b>WATER, SEDIMENT</b>						
		Local PEC in surface water during emission episode (dissolved)	0.0158			[mg l <sup>-1</sup> ]		
		Annual average local PEC in surface water (dissolved)	0.0157			[mg l <sup>-1</sup> ]		
		Local PEC in fresh-water sediment during emission episode	0.27			[mg kg wwt <sup>-1</sup> ]		



# Citric acid

Revision date: 02 Dec 2013

	Local PEC in seawater during emission episode (dissolved)	0.0194	[mg l <sup>-1</sup> ]
	Annual average local PEC in seawater (dissolved)	0.0162	[mg l <sup>-1</sup> ]
	Local PEC in marine sediment during emission episode	0.331	[mg kg wwt <sup>-1</sup> ]
	<b>SOIL, GROUNDWATER</b>		
	Local PEC in agric. soil (total) averaged over 30 days	0.106	[mg kg wwt <sup>-1</sup> ]
	Local PEC in agric. soil (total) averaged over 180 days	0.347	[mg kg wwt <sup>-1</sup> ]
	Local PEC in grassland (total) averaged over 180 days	0.0139	[mg kg wwt <sup>-1</sup> ]
	Local PEC in pore water of agricultural soil	5.23 x 10 <sup>-4</sup>	[mg l <sup>-1</sup> ]
	Local PEC in pore water of grassland	2.09 x 10 <sup>-4</sup>	[mg l <sup>-1</sup> ]
	Local PEC in groundwater under agricultural soil	5.23 x 10 <sup>-4</sup>	[mg l <sup>-1</sup> ]



# Citric acid

Revision date: 02 Dec 2013

Substance / User identity		
	Registration number(s)	01-2119457026-42-xxxx
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	4、 Personal care use
	Processes and activities covered by the exposure scenario	SU20,SU21,SU22, PROC 10, PROC 11, PROC 19
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Worker All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	solid
	Concentration of substance in preparation or article	
	Other relevant operational conditions of use	<p>The EU TGD A-Table A4.1 gives the releases of cosmetics to air and wastewater as 0 and 100% respectively. This seems reasonable, given that citrates are non-volatile and highly water soluble. It is also in agreement with Colipa's assessment of the fate of non-volatile components of cosmetics (Colipa 2008).</p> <p>The TGD defaults and REACH environmental release category (ERC8a) assume that if a substance is used widely across the EU, the fraction of the production volume used in the standard EU Region is 10%. For cosmetics, the fraction of the main local source (fmainsource) is 0.0005 (HERA, 2005, page 27). This is equivalent to saying that use in a region is evenly distributed. The number of days of use is 365 per year. Therefore, for 7500 tpa of citric acid in personal care products used widely across the EU, the estimated release of citric acid to a particular default-sized local waste water treatment plant is at most:</p> $7\ 500\ 000\ \text{kg/y} \times 0.1 \times 0.0005 / 365\ \text{d/y} = 1.03\ \text{kg/d}$
Risk management measures:		
2.1	Control of worker exposure	
	Technical conditions and measures at process level (source) to prevent release	No risk management measures are possible for personal care use in respect of the environment.
	Technical conditions and measures to control dispersion from source towards the worker	No risk management measures are possible for personal care use in respect of the environment.
	Engineering controls:	No risk management measures are possible for personal care use in respect of the environment.
	Organisational measures to prevent/limit releases, dispersion and exposure	No risk management measures are possible for personal care use in respect of the environment.
	Conditions and measures related to personal protection, hygiene and health evaluation	No risk management measures are possible for personal care use in respect of the environment.
Information on estimated exposure and Downstream-user guidance		
3	Environmental releases	Predicted Environmental Concentrations have been determined using EUSES 2.1.1. The EUSES program implements the environmental exposure models described in REACH Technical Guidance Chapter R16. Default model parameters



# Citric acid

Revision date: 02 Dec 2013

		<p>have been used with the following exceptions:          The basis of local and regional production tonnages is to consider the sizes of the largest sites in the EU relative to the total tonnage as follows:          Production volume in EU: 7,500,000 tonnes          Regional tonnage: 750,000 tonnes          Fraction of main local source: 0.0005          Local tonnage: 1.03 tonnes per day          Number of days: 365</p> <p>The contribution of local releases to the regional concentration has been considered using the appropriate calculation in EUSES 2.1.1. Table 9.33 shows the Predicted Environmental Concentrations. Due to the ready-biodegradability of citric acid it has not been considered necessary to define a PEC. The low log Kow and ready biodegradability indicate that bioaccumulation is not a concern for citric acid. Therefore, the assessment of secondary poisoning is not considered further.</p>																																							
	<p>Summary of Predicted Exposure Concentrations</p>	<table border="1"> <thead> <tr> <th></th> <th>PEC</th> <th>unit</th> </tr> </thead> <tbody> <tr> <td colspan="3"><b>AIR</b></td> </tr> <tr> <td>Annual average local PEC in air (total)</td> <td><math>5.45 \times 10^{-16}</math></td> <td>[mg.m<sup>-3</sup>]</td> </tr> <tr> <td colspan="3"><b>WATER, SEDIMENT</b></td> </tr> <tr> <td>Local PEC in surface water during emission episode (dissolved)</td> <td><math>1.59 \times 10^{-2}</math></td> <td>[mg l<sup>-1</sup>]</td> </tr> <tr> <td>Annual average local PEC in surface water (dissolved)</td> <td><math>1.59 \times 10^{-2}</math></td> <td>[mg l<sup>-1</sup>]</td> </tr> <tr> <td>Local PEC in fresh-water sediment during emission episode</td> <td><math>2.71 \times 10^{-1}</math></td> <td>[mg kg wwt<sup>-1</sup>]</td> </tr> <tr> <td>Local PEC in seawater during emission episode (dissolved)</td> <td><math>1.48 \times 10^{-3}</math></td> <td>[mg l<sup>-1</sup>]</td> </tr> <tr> <td>Annual average local PEC in seawater (dissolved)</td> <td><math>1.48 \times 10^{-3}</math></td> <td>[mg l<sup>-1</sup>]</td> </tr> <tr> <td>Local PEC in marine sediment during emission episode</td> <td><math>2.53 \times 10^{-2}</math></td> <td>[mg kg wwt<sup>-1</sup>]</td> </tr> <tr> <td colspan="3"><b>SOIL, GROUNDWATER</b></td> </tr> <tr> <td>Local PEC in agric. soil (total) averaged over 30 days</td> <td><math>3.02 \times 10^{-2}</math></td> <td>[mg kg wwt<sup>-1</sup>]</td> </tr> <tr> <td>Local PEC in agric. soil (total) averaged over</td> <td><math>9.89 \times 10^{-3}</math></td> <td>[mg kg wwt<sup>-1</sup>]</td> </tr> </tbody> </table>		PEC	unit	<b>AIR</b>			Annual average local PEC in air (total)	$5.45 \times 10^{-16}$	[mg.m <sup>-3</sup> ]	<b>WATER, SEDIMENT</b>			Local PEC in surface water during emission episode (dissolved)	$1.59 \times 10^{-2}$	[mg l <sup>-1</sup> ]	Annual average local PEC in surface water (dissolved)	$1.59 \times 10^{-2}$	[mg l <sup>-1</sup> ]	Local PEC in fresh-water sediment during emission episode	$2.71 \times 10^{-1}$	[mg kg wwt <sup>-1</sup> ]	Local PEC in seawater during emission episode (dissolved)	$1.48 \times 10^{-3}$	[mg l <sup>-1</sup> ]	Annual average local PEC in seawater (dissolved)	$1.48 \times 10^{-3}$	[mg l <sup>-1</sup> ]	Local PEC in marine sediment during emission episode	$2.53 \times 10^{-2}$	[mg kg wwt <sup>-1</sup> ]	<b>SOIL, GROUNDWATER</b>			Local PEC in agric. soil (total) averaged over 30 days	$3.02 \times 10^{-2}$	[mg kg wwt <sup>-1</sup> ]	Local PEC in agric. soil (total) averaged over	$9.89 \times 10^{-3}$	[mg kg wwt <sup>-1</sup> ]
	PEC	unit																																							
<b>AIR</b>																																									
Annual average local PEC in air (total)	$5.45 \times 10^{-16}$	[mg.m <sup>-3</sup> ]																																							
<b>WATER, SEDIMENT</b>																																									
Local PEC in surface water during emission episode (dissolved)	$1.59 \times 10^{-2}$	[mg l <sup>-1</sup> ]																																							
Annual average local PEC in surface water (dissolved)	$1.59 \times 10^{-2}$	[mg l <sup>-1</sup> ]																																							
Local PEC in fresh-water sediment during emission episode	$2.71 \times 10^{-1}$	[mg kg wwt <sup>-1</sup> ]																																							
Local PEC in seawater during emission episode (dissolved)	$1.48 \times 10^{-3}$	[mg l <sup>-1</sup> ]																																							
Annual average local PEC in seawater (dissolved)	$1.48 \times 10^{-3}$	[mg l <sup>-1</sup> ]																																							
Local PEC in marine sediment during emission episode	$2.53 \times 10^{-2}$	[mg kg wwt <sup>-1</sup> ]																																							
<b>SOIL, GROUNDWATER</b>																																									
Local PEC in agric. soil (total) averaged over 30 days	$3.02 \times 10^{-2}$	[mg kg wwt <sup>-1</sup> ]																																							
Local PEC in agric. soil (total) averaged over	$9.89 \times 10^{-3}$	[mg kg wwt <sup>-1</sup> ]																																							



# Citric acid

Revision date: 02 Dec 2013

	180 days		
	Local PEC in grassland (total) averaged over 180 days	$3.95 \times 10^{-3}$	[mg kg wwt <sup>-1</sup> ]
	Local PEC in pore water of agricultural soil	$1.49 \times 10^{-4}$	[mg l <sup>-1</sup> ]
	Local PEC in pore water of grassland	$5.97 \times 10^{-5}$	[mg l <sup>-1</sup> ]
	Local PEC in groundwater under agricultural soil	$1.49 \times 10^{-4}$	[mg l <sup>-1</sup> ]
Other environmental releases	<p>The EUSES model uses the Simple Treat sewage treatment model to predict the fate of a substance in the STP, based on the physicochemical and biodegradation properties. For citric acid, SimpleTreat predicts the following:</p> <p>12.6 % to water:</p> <p>0.112 % to air:</p> <p>0.0154 % to sludge:</p> <p>87.3 % degraded.</p> <p>Sludge from WWTPs may be spread on agricultural soil.</p> <p>The dilution factor of 900 and 1000 (in the receiving water) have been applied for fresh water and marine water respectively, as there is no information on specific hydrodynamic conditions.</p> <p>There is no direct release to the terrestrial compartment on a local scale as biosludge from on-site waste water treatment is disposed of via incineration or landfill. However, due to use of municipal WWTP by some EU production sites, spreading of sludge on agricultural soil is included as a reasonable worst case.</p>		



# Citric acid

Revision date: 02 Dec 2013

Substance / User identity				
Registration number(s)	01-2119457026-42-xxxx			
Substance identity	CAS#77-92-9; EC#201-069-1			
1	Short title of the exposure scenario	5. Use of citric acid in cleaning products		
	Processes and activities covered by the exposure scenario	SU3, SU21, SU22, PROC1, PROC 2, PROC 4, PROC 5, PROC 7, PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 11, PROC 13, PROC 19		
2	Operational conditions and risk management measures			
	Duration an frequency of use			
	Worker All applicable PROCs	>4h		
	Physical form of substance: under conditions of use it is used as a liquid.	May be liquid or solid.		
	Concentration of substance in preparation or article			
Other relevant operational conditions of use	<p>No measured data are available for releases to air and waste water during the use of citric acid in cleaning products. Releases are therefore estimated on the basis of information in the public domain.</p> <p>Citric acid and citrates are used in a variety of cleaning products but generally in aqueous solution. The most likely release route will, therefore, be to waste water via rinsing to drain in-use, spillage, clean out or discharge of cleaning baths or liquors. Indeed, releases to waste water can be assumed to be 100%, since all the citric acid/citrate will eventually be washed to drain. This may be an overestimate since it does not allow for any of the substance to be either released to air (extremely unlikely) during the process or to adsorb to a surface on drying or to a cleaning implement (e.g., cloth) which may be landfilled.</p> <p>The release of citrates from use in cleaning products in industrial, professional and consumer use can be estimated. The TGD defaults and REACH environmental release category (ERC8a) assume that if a substance is used widely across the EU, the fraction of the production volume used in the standard EU Region is 10%. For cleaning products, the fraction of the regional tonnage discharging to a particular waste water treatment plant can be estimated as 0.0005 (HERA, 2005). The number of days of use is 365 per year. Therefore, for 100,000 tpa of citric acid in cleaning products used widely across the EU, the estimated release of citrates to a particular default-sized local waste water treatment plant is at most:</p> $100,000,000 \text{ kg/y} \times 0.1 \times 0.0005 / 365 \text{ d/y} = 13.7 \text{ kg/d}$ <p>= (Amount of citrates used in cleaning products per year x fraction to water x fraction in the region x fraction of main local source) / number of days per year</p> <p>The research carried out by the HERA project was thorough and accepted by the EU authorities as valid.</p>			
Risk management measures:				
2.1	Control of worker exposure			
	Containment and local exhaust ventilation	Information type	Data field	Explanation
		Containment plus good work practice required	Yes	General good hygiene and housekeeping
Local exhaust ventilation required plus good work practise	No			



# Citric acid

Revision date: 02 Dec 2013

2.2	Personal protective equipment (PPE)	Information type	Data field	Explanation
		Skin protection	Protective gloves	
		Eye protection	Safety glasses	
		Clothing	Working clothing worn.	
	Other risk management measures related to workers	N/A		
	Risk management measures related to environmental emissions from industrial sites	Information type	Data field	Explanation
		Onsite pre-treatment of waste water	Yes	Neutralisation
		Resulting fraction of initially applied amount in waste water released from site to the external sewage system		On-site biological waste treatment is expected to remove a high proportion of citric acid, as the substance is highly biodegradable.
		Air emission abatement	No measured data	
		Resulting fraction of applied amount in waste gas released to environment	No measured data	
		Onsite waste treatment	No measured data	Secondary biological treatment
Fraction of initially applied amount sent to external waste treatment. This is the sum of direct losses from processes to waste, and the residues from onsite waste water and waste gas treatment.		No measured data		
Municipal or other type of external waste water treatment		None	None	
Effluent (of the waste water treatment plant) discharge rate		2000000 l/d	Default for a standard WWTP	
Recovery of sludge for agriculture or horticulture	Yes	Dried sludge may be sold as an approved agricultural fertiliser		
Onsite pre-treatment of waste water	Yes	Neutralisation		
Control of environmental exposure				



# Citric acid

Revision date: 02 Dec 2013

Frequency and duration of use			
Duration, frequency and amount	Information type	Data field	Explanation
	Used amount of substance per day	200,000 kg/d	Generic information
	Duration of exposure per day at workplace [for one worker]	>4 hours (all PROCs)	For some applications/setting exposure times may be significantly less
	Frequency of exposure at workplace [for one worker]	Once per day	For some applications/settings with shorter duration exposures, multiple exposures may occur in a single day
	Annual amount used per site	10 kg/d	0.00005 (10% in region, plus 0.0005 fraction of main local source from HERA)
	Emission days per site	365 d/y	Default for ERC8
Information on estimated exposure and Downstream-user guidance			
3	Exposure estimation and reference to its source:		



# Citric acid

Revision date: 02 Dec 2013

Dermal exposure estimates (based on ECETOC TRA model) for cleaning and maintenance	Process category	Description	Predicted exposure ( $\mu\text{g}/\text{cm}^2/\text{day}$ )	Exposed skin surface area ( $\text{cm}^2$ )	Dermal exposure ( $\text{mg}/\text{kg}/\text{day}$ ) <sup>a</sup>
	PROC8a	Transfer from/to large vessels (non-dedicated)	1000	960	13.7
	PROC8b	Transfer from/to large vessels (dedicated)	1000	480	6.9
	PROC9	Transfer to small containers	1000	480	6.9
	PROC7	Industrial spraying	100	1500	2.14
	PROC10	Roller application or brushing	2000	960	27.4
	PROC13	Dipping or pouring	2000	480	13.7
	(a) Calculated assuming a default bodyweight of 70 kg for workers				



# Citric acid

Revision date: 02 Dec 2013

Inhalation exposure estimates (based on ECETOC TRA model) for cleaning and maintenance products	Process category	Description	Predicted exposure ( $\mu\text{g}/\text{cm}^2/\text{day}$ )	Exposed skin surface area ( $\text{cm}^2$ )	Dermal exposure ( $\text{mg}/\text{kg}/\text{day}$ ) <sup>a</sup>
	PROC8a	Transfer from/to large vessels (non-dedicated)	0.063	0.5	0.07
	PROC8b	Transfer from/to large vessels (dedicated)	0.012	0.1	0.014
	PROC9	Transfer to small containers	0.012	0.1	0.01
	PROC7	Spraying in industrial settings and applications	0.63	5	0.71
	PROC10	Roller application or brushing	0.063	0.5	0.07
	PROC13	Dipping or pouring	0.012	0.1	0.014
	Summary of long-term exposure concentration to workers	Routes of exposure	Concentrations	Justification	
Dermal local exposure (in $\mu\text{g}/\text{cm}^2$ )		12	ECETOC TRA prediction for PROC10; multiplied by a dermal uptake factor of 0.006.		
Dermal systemic exposure (in $\text{mg}/\text{kg}$ bw/d)		0.16	ECETOC TRA prediction for PROC10; multiplied by a dermal uptake factor of 0.006.		
Inhalation exposure (in $\text{mg}/\text{m}^3$ )/8h workday		5	ECETOC TRA prediction for PROC7		
Inhalation exposure (in $\text{mg}/\text{kg}/\text{d}$ )/8h workday		0.71	ECETOC TRA prediction for PROC7		
4	Operational conditions related to available dilution capacity and characteristics of exposed humans				
	Occupational exposure Operational conditions related to respiration and skin contact	Information type	Data field	Explanation	
		Respiration volume under conditions of use	10 $\text{m}^3/\text{d}$	Default for workers, light activity	



# Citric acid

Revision date: 02 Dec 2013

		Area of skin contact with the substance under conditions of use	480 cm <sup>2</sup> 1500 cm <sup>2</sup> 960 cm <sup>2</sup> 480 cm <sup>2</sup> 480 cm <sup>2</sup> 960 cm <sup>2</sup> 1500 cm <sup>2</sup> 480 cm <sup>2</sup> 1980 cm <sup>2</sup>	ECETOC TRA default: PROC5: PROC7: PROC8a: PROC8b: PROC9 PROC10 PROC11 PROC13 PROC19
		Body weight	70 kg	Default for workers
Operational conditions related to respiration, skin contact and ingestion for the general public	Information type	Data field	Explanation	
	Skin contact area	960 cm <sup>2</sup>	ConsExpo default	
	Mouth contact area	-	Not applicable – no oral exposure	
	Respiration volume under conditions of use	26 m <sup>3</sup>	Default: Light activity 26 m <sup>3</sup> /24 h	
	Room size and ventilation rate	20m <sup>3</sup> ; exchange per hour 0.6 h <sup>-1</sup>	ConsExpo defaults	
	Body weight	65 kg	Default adult bodyweight	
Predicted Exposure Concentrations of Environmental releases		PEC	unit	
	<b>AIR</b>			
	Annual average local PEC in air (total)	1.30 x 10 <sup>-15</sup>	[mg.m <sup>-3</sup> ]	
	<b>WATER, SEDIMENT</b>			
	Local PEC in surface water during emission episode (dissolved)	2.48 x 10 <sup>-2</sup>	[mg l <sup>-1</sup> ]	
	Annual average local PEC in surface water (dissolved)	2.48 x 10 <sup>-2</sup>	[mg l <sup>-1</sup> ]	
	Local PEC in fresh-water sediment during emission episode	4.23 x 10 <sup>-1</sup>	[mg kg wwt <sup>-1</sup> ]	
	Local PEC in seawater during emission episode (dissolved)	2.37 x 10 <sup>-3</sup>	[mg l <sup>-1</sup> ]	
	Annual average local PEC in seawater (dissolved)	2.37 x 10 <sup>-3</sup>	[mg l <sup>-1</sup> ]	
	Local PEC in marine sediment during	4.05 x 10 <sup>-2</sup>	[mg kg wwt <sup>-1</sup> ]	





# Citric acid

Revision date: 02 Dec 2013

		emission episode		
		<b>SOIL, GROUNDWATER</b>		
		Local PEC in agric. soil (total) averaged over 30 days	$4.02 \times 10^{-1}$	[mg kg wwt <sup>-1</sup> ]
		Local PEC in agric. soil (total) averaged over 180 days	$1.32 \times 10^{-1}$	[mg kg wwt <sup>-1</sup> ]
		Local PEC in grassland (total) averaged over 180 days	$5.27 \times 10^{-2}$	[mg kg wwt <sup>-1</sup> ]
		Local PEC in pore water of agricultural soil	$1.99 \times 10^{-3}$	[mg l <sup>-1</sup> ]
		Local PEC in pore water of grassland	$7.95 \times 10^{-4}$	[mg l <sup>-1</sup> ]
		Local PEC in groundwater under agricultural soil	$1.99 \times 10^{-3}$	[mg l <sup>-1</sup> ]



## Citric acid

Revision date: 02 Dec 2013

Substance / User identity		
	Registration number(s)	01-2119457026-42-xxxx
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	6、 Use in paper
	Processes and activities covered by the exposure scenario	SU3, SU6 PROC 5, PROC 8a
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Worker All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	solid
	Concentration of substance in preparation or article	
	Other relevant operational conditions of use	N/A
Risk management measures:		
2.1	Control of worker exposure	Following the REACH descriptor system, the following product type is covered by this generic scenario: Paper and board dye, finishing and impregnation products: including bleaches and other processing aids (PC26).
	Technical conditions and measures at process level (source) to prevent release	N/A
	Technical conditions and measures to control dispersion from source towards the worker	N/A
	Engineering controls:	N/A
	Organisational measures to prevent/limit releases, dispersion and exposure	N/A
	Conditions and measures related to personal protection, hygiene and health evaluation	N/A
2.2	Control of environmental exposure	
	Frequency and duration of use	
	Waste water flow	N/A
	Dilution factor	
	Emission factor to waste water Release fraction	N/A
	Conditions and measures related to external recovery of waste	N/A

# Citric acid

Revision date: 02 Dec 2013

Information on estimated exposure and Downstream-user guidance	
3	Exposure estimation and reference to its source: N/A
4	Guidance to DU to evaluate whether he works inside the boundaries set by the ES Occupational exposure N/A
	<p>Environmental emissions</p> <p>Citric acid is used in the cleaning of papermaking machines and to prevent build up of deposits. It is added to the pulp slurry prior to bleaching to control paper staining by sequestering metal ions. Cleaning applications are covered under another exposure scenario; this document covers use of citrate as a processing aid in the paper-making industry.</p> <p>This generic scenario makes use of the following documents:</p> <p style="padding-left: 40px;">OECD Emission Scenario Documents on Kraft, Non-Integrated and Recovered Pulp Mills.</p> <p>This covers the use of citrate as a process aid in the paper-making industry. It is possible that a small amount of citrate is incorporated into the finished paper products. However, it is considered that the amount of citrate that ends up in articles and could be released (resulting in consumer exposure) is likely to be negligible.</p> <p>The amount of citric acid believed to be used in this application is at most 1000 tpa. The industrial use per site is unknown. However, a default approach would be to consider 10 paper mills in a single region, operating over 300 days per year. The substance is not mixed into pulp, but is applied to machinery. A loss of 2% is a realistic maximum.</p> <p>This gives a daily release of</p> $100 \text{ t} \times 1000 \text{ kg/t} \times 0.02 / 300 \text{ d} = 6.7 \text{ kg/d}$ <p>For the environment, the amounts passing to waste are very likely to be less than those from the ES 1-5. Therefore there is no need to complete an exposure assessment at a local scale with full details of PEC values etc.</p> <p>However, a regional release of 67 kg/d to waste water will be added to the model.</p> <p>For human health worker exposure at paper mills will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.</p>

# Citric acid

Revision date: 02 Dec 2013

Substance / User identity		
	Registration number(s)	01-2119457026-42-xxxx
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	7. Use in construction
	Processes and activities covered by the exposure scenario	SU3, SU21, SU22, SU2, SU10, SU19, PROC 2, PROC 4, PROC 5, PROC 7, PROC 8a, PROC 8b, PROC 10, PROC 11. PROC 13, PROC 14, PROC 19, PROC 21, PROC 24
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Worker All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	solid
	Concentration of substance in preparation or article	N/A
	Other relevant operational conditions of use	N/A
Risk management measures:		
2.1	Control of worker exposure	<p>Following the REACH descriptor system, the following product types are covered by this generic scenario: PC10 (Building and construction preparations not covered elsewhere).</p> <p>The following substances are used in construction materials: citric acid and trisodium citrate.</p> <p>Citrates can be used to retard the setting rate of cement and reduce the amount of water needed. They may therefore be added to concrete, mortar, plaster and render formulations. The concentration in these products is generally low (&lt;1%).</p>
	Technical conditions and measures at process level (source) to prevent release	N/A
	Conditions and measures related to personal protection, hygiene and health evaluation	N/A
2.2	Control of environmental exposure	
	Frequency and duration of use	
	Use per site Duration of emission Waste water flow Dilution factor	N/A
	Emission factor to waste water Release fraction	N/A
	Environment factors not influenced by	N/A

# Citric acid

Revision date: 02 Dec 2013

	risk management	
	Other given operational conditions affecting environmental exposure	
	Technical conditions and measures at process level (source) to prevent release	No specific measures are considered.
	Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil	N/A
	Organizational measures to prevent/limit release from site	N/A
	Conditions and measures related to municipal sewage treatment plant	N/A
	Conditions and measures related to external treatment of waste for disposal	N/A
	Conditions and measures related to external recovery of waste	none
Information on estimated exposure and Downstream-user guidance		
3	Exposure estimation and reference to its source:	
	Occupational exposure: Dermal Inhalation	N/A
4	Guidance to DU to evaluate whether he works inside the boundaries set by the ES	
	Occupational exposure	N/A
	Environmental emissions	<p>This document provides an environmental generic exposure scenario for substances used in construction materials. This generic scenario makes use of the following documents:</p> <p style="text-align: center;">EU Technical Guidance Document (TGD) emission scenario document. REACH Technical Guidance.</p> <p>The amount of citric acid believed to be used in this application is at most 1500 tpa. The industrial use per site is unknown, but should be considered as a widely dispersed use. In the worst case a release of the entire tonnage to the region could be included, i.e. 1500 tpa. Of this, part will be released to industrial soil (90%) and part to waste water (10%).</p> <p>A regional release of <math>150 \times 1000/365 = 411</math> kg/d to waste water will be added to the model, and 3699 kg/d to industrial soil will be included.</p> <p>For human health worker exposure at construction sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.</p>



# Citric acid

Revision date: 02 Dec 2013

Substance / User identity	
	Registration number(s) 01-2119457026-42-xxxx
	Substance identity CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario 8. Use in polymers and plastics
	Processes and activities covered by the exposure scenario SU3,SU11,SU12, PROC 3, PROC 5, PROC 8a, PROC 8b
2	Operational conditions and risk management measures
	Duration an frequency of use
	Physical form of substance: under conditions of use it is used as a liquid. solid
	Concentration of substance in preparation or article N/A
	Other relevant operational conditions of use <p>Please also note that under acidic conditions (pH&lt;7), sulfur dioxide can be formed. Please ensure compliance with the existing occupational exposure limit as recommended by SCOEL (2008) for sulfur dioxide of 0.5 ppm (TWA, 8h) respectively 1 ppm (STEL, 15 min).</p> <p>Polyolefin foams are used for a variety of applications such as automotive, construction, food packaging, sport and leisure, and many other industrial and consumer uses. They usually have a high strength to weight ratio and are manufactured in a variety of processes and in low density (25 - 250 kg/m<sup>3</sup>) or high density (250 - 700 kg/m<sup>3</sup>) versions, or even in densities as low as 16 kg/m<sup>3</sup> for polystyrene. All current extrusion processes involve the following steps: melting, mixing with blowing agents, cooling of melt, expansion and degassing/aging. The steps in this process can be realized in different configurations of equipment, e.g., with long single-screw extruders, twin-screw extruders, or tandem extruder lines.</p> <p>Both citric acid (or citrate salt) and (bi)carbonate may be surface-treated with, for example, a fatty acid ester to make them compatible with the polyolefin. A concentrated master batch of the formulated foaming agent in polymer at loading levels of from about 5% to about 50% actives may then be prepared. The master batch is added to the polymer melt which is to be foamed such that the blowing agents are at 0.1 to 2.0% active levels in the final formulation [US 5,302,455 and refs. therein].</p> <p>By-products of this reaction are mono-, di-, and/or trisodium citrate, in combination with other sodium salts, which will still be present within the foamed polymer. These residues are typically present at around 50 wt.% of the initial foaming agent formulation, which is equivalent to &lt;1 wt.% of the total foamed polymer in most cases [RAPRA, 2004].</p>
Risk management measures:	
2.1	Control of worker exposure
	Technical conditions and measures at process level (source) to prevent release N/A
	Technical conditions and measures to control dispersion from source towards the worker N/A
	Engineering controls:
	Organisational measures to prevent/limit releases, dispersion and N/A

# Citric acid

Revision date: 02 Dec 2013

	exposure	
	Conditions and measures related to personal protection, hygiene and health evaluation	
2.2	Control of environmental exposure	
	Use per site Duration of emission Waste water flow Dilution factor	N/A
	Release of citric acid	<p>Losses from conversion, service life and disposal for chemical blowing agents are considered to be zero as the additive is destroyed during the conversion process. Thus, for 200 tpa of citrates used in plastics applications, assumed to be used at 10 sites across Europe, the local losses to water air and solid waste are:</p> <p>The REACH defaults for ERC6d are for the production on 300 days per year if the tonnage of the product is &gt;5000 tpa [ECHA, 2009]. Citrate is present at &lt;1% in plastics applications (see Section 2.1.1), therefore, the total production volume is approx. 100,000 tpa. Therefore, the maximum daily releases are as follows:</p> <p>Water: <math>20 \text{ t} \times 1000 \text{ kg/t} \times (0.0065) / 300 = 0.43 \text{ kg/d}</math>  Air: 0</p> <p>For the environment, the amounts passing to waste are very likely to be less than those from the ES 1-5. Therefore there is no need to complete an exposure assessment at a local scale with full details of PEC values etc.</p> <p>However, a regional release of 0.35 kg/d to waste water will be added to the model, and similarly 3.18 kg/d to the continental scale.</p>
	Environment factors not influenced by risk management	N/A
	Other given operational conditions affecting environmental exposure	N/A
	Technical conditions and measures at process level (source) to prevent release	N/A
	Conditions and measures related to external recovery of waste	none
Information on estimated exposure and Downstream-user guidance		
3	Exposure estimation and reference to its source:	
	Occupational exposure: Dermal Inhalation	Not relevant
4	Guidance to DU to evaluate whether he works inside the boundaries set by the ES	
	Occupational exposure	For human health worker exposure at construction sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.

# Citric acid

Revision date: 02 Dec 2013

	Environmental emissions	N/A
--	-------------------------	-----



# Citric acid

Revision date: 02 Dec 2013

Substance / User identity		
Registration number(s)	01-2119457026-42-xxxx	
Substance identity	CAS#77-92-9; EC#201-069-1	
1	Short title of the exposure scenario	9、 Use in the oil industry
	Processes and activities covered by the exposure scenario	SU3 , SU2 PROC 3, PROC 4, PROC 5,
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Physical form of substance: under conditions of use it is used as a liquid.	solid
	Concentration of substance in preparation or article	20-50%
	Other relevant operational conditions of use	<p>In the oil industry, citric acid is often used for oil-well acidizing to prevent the formation of iron hydroxide [APAC]. Oil well acidizing is the term used for the application of hydrochloric acid (93-149°C) to remove tough wellbore scale [McGraw-Hill].</p> <p>Oxidation reactions, which occur in wells injected with HCl, cause formation of insoluble iron precipitates. The pumping operations are thus interrupted by these gels, and hence, citric acid is added to prevent gel formation [APAC].</p> <p>Oil producing well formations can become plugged with acid soluble minerals and restrict production [Gewanter, Herman L. et al]. Production can be increased by forcing acid to dissolve the minerals [Gewanter, Herman L. et al]. The acids readily dissolve the iron and iron from the well casing and the formation [Gewanter, Herman L. et al]. However, water and carbon dioxide in the formation, which allows for the re-precipitation of the iron to ferric hydroxide above the wellbore [Gewanter, Herman L. et al]. Certain chemicals must be added at this point to maintain it in a soluble state [et al].</p>
Risk management measures:		
2.1	Control of consumers exposure	Not relevant
	Human factors not influenced by risk management	Not relevant
	Other given operational conditions affecting consumers exposure	Not relevant
	Conditions and measures related to information and behavioural advice to consumers	Not relevant
	Conditions and measures related to personal protection, hygiene and health evaluation	Not relevant
2.2	Control of environmental exposure	
	Frequency and duration of use	
	waste water Release	<p>Control of the re-precipitation of iron and the pH, as the acid is spent, can be achieved by the sequestration by organic chelants and the reduction to soluble ferrous iron [Gewanter, Herman L. et al]. Citric acid is a useful organic chelant and is used for this purpose [Gewanter, Herman L. et al]. Other chelants may include gluconic acid, the tetrasodium salt of ethylenediaminetetraacetic acid (EDTA), and the trisodium salt of nitrilotriacetic acid (NTA) [Gewanter, Herman L. et al].</p> <p>This is a widely dispersed use but in the worst case it can be envisaged that the</p>



# Citric acid

Revision date: 02 Dec 2013

		entire tonnage could pass to surface marine water. This equates to  100 t x 1000 kg/t /365 = 274 kg/d to the regional surface water  900 t x 1000 kg/t /365 = 2740 kg/d to the continental surface water
	Environment factors not influenced by risk management	None
	Conditions and measures related to external treatment of waste for disposal	None
	Conditions and measures related to external recovery of waste	none
Information on estimated exposure and Downstream-user guidance		
3	Exposure estimation and reference to its source:	
	Human exposure:	For human health worker exposure at oil production sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.
4	Guidance to DU to evaluate whether he works inside the boundaries set by the ES	
	Consumer exposure	N/A
	Environmental emissions	N/A

# Citric acid

Revision date: 02 Dec 2013

Substance / User identity				
Registration number(s)	01-2119457026-42-xxxx			
Substance identity	CAS#77-92-9; EC#201-069-1			
1	Short title of the exposure scenario	10. Use in textiles		
	Processes and activities covered by the exposure scenario	SU3,SU5 PROC8a,PROC8b, PROC10, PROC13, PROC22		
2	Operational conditions and risk management measures			
	Duration an frequency of use			
	Worker All applicable PROCs	>4h		
	Physical form of substance: under conditions of use it is used as a liquid.	Solid.		
	Concentration of substance in preparation or article			
Other relevant operational conditions of use	<p>No measured data are available for releases of citric acid to air and waste water from textile production sites. Releases are therefore estimated on the basis of information in the public domain.</p> <p>Potential exposure to humans and especially the environment is dependent on the intended function of the substance, as well as the substrates and processes used. Functional finishing agents and other chemically reactive substances are intended to be consumed during use, therefore the amount released is related to efficiency of the process. On the other hand, non-reacting substances (e.g. processing aids) are not consumed and will ultimately be lost to air or waste water, depending on their function and physicochemical properties. In virtually all cases, it is expected that citric acid or citrate salts, as process aids, will be lost to waste water.</p> <p>The annual tonnage of 300 t is considered to be used at 40% in the region. The largest site is estimated to use around 6 tpa. If all passed to waste water this is: 6 t x 1000 kg/t / 300 = 20 kg/d.</p>			
Risk management measures:				
2.1	Control of worker exposure	For human health worker exposure at textile production sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.		
	Risk management measures for industrial site	Information type	Data field	Explanation
		Onsite pre-treatment of waste water	Yes	Neutralisation
	Resulting fraction of initially applied amount in waste water released from site to the external sewage system		On-site biological waste treatment (where present) is expected to remove a high proportion of citric acid, as the substance is highly biodegradable. However, on-site biological waste treatment is not assumed as it is not known that this is always present.	

# Citric acid

Revision date: 02 Dec 2013

	Air emission abatement	No measured data	
	Resulting fraction of applied amount in waste gas released to environment	No waste gases	
	Onsite waste treatment	No measured data	Secondary biological treatment may be present but this is not assumed in the scenario
	Fraction of initially applied amount sent to external waste treatment. This is the sum of direct losses from processes to waste, and the residues from onsite waste water and waste gas treatment.	No measured data	
	Municipal or other type of external waste water treatment	None	None
	Effluent (of the waste water treatment plant) discharge rate	2000000 l/d	Default for a standard WWTP
	Recovery of sludge for agriculture or horticulture	Yes	
	Personal protective equipment (PPE)	N/A	
Other risk management measures related to workers	N/A		
2.2	Control of environmental exposure		
	Frequency and duration of use		
	Duration, frequency and amount		
Information on estimated exposure and Downstream-user guidance			
3	Exposure estimation and reference to its source:		
	Releases to air	As the citrates are solids with high water solubility, losses to air are considered to be negligible.	

# Citric acid

Revision date: 02 Dec 2013

	Releases to waste water	Citric acid and citrates are used in textile and leather treatment in aqueous solution. The most likely release route will be to waste water via spillage, clean out and discharge of spent treatment baths and liquors recovered in handling fabrics after treatment. Indeed, releases to waste water can be assumed to be 100%, since all the citric acid/citrate may be washed to drain.			
	Technical fate of substance and losses from process/use to waste, waste water and air	<b>Information</b>	<b>Data field</b>	<b>Explanation</b>	
Fraction of applied amount lost from process/use to waste gas		0 kg/kg	See text		
Fraction of applied amount lost from process/use to waste water		1 kg/kg	See text		
Predicted Exposure Concentrations of Environmental releases			PEC	unit	
		<b>AIR</b>			
		Annual average local PEC in air (total)	1.56 x 10 <sup>-15</sup>	[mg.m <sup>-3</sup> ]	
		<b>WATER, SEDIMENT</b>			
		Local PEC in surface water during emission episode (dissolved)	2.92 x 10 <sup>-2</sup>	[mg l <sup>-1</sup> ]	
		Annual average local PEC in surface water (dissolved)	2.67 x 10 <sup>-2</sup>	[mg l <sup>-1</sup> ]	
		Local PEC in fresh-water sediment during emission episode	4.98 x 10 <sup>-1</sup>	[mg kg wwt <sup>-1</sup> ]	
		Local PEC in seawater during emission episode (dissolved)	1.01 x 10 <sup>-1</sup>	[mg l <sup>-1</sup> ]	
		Annual average local PEC in seawater (dissolved)	8.35 x 10 <sup>-2</sup>	[mg l <sup>-1</sup> ]	
		Local PEC in marine sediment during emission episode	1.73	[mg kg wwt <sup>-1</sup> ]	
		<b>SOIL, GROUNDWATER</b>			
		Local PEC in agric. soil (total) averaged over 30 days	5.87 x 10 <sup>-1</sup>	[mg kg wwt <sup>-1</sup> ]	
		Local PEC in agric. soil (total) averaged over 180 days	1.93 x 10 <sup>-1</sup>	[mg kg wwt <sup>-1</sup> ]	



## Citric acid

Revision date: 02 Dec 2013

	Local PEC in grassland (total) averaged over 180 days	$7.70 \times 10^{-2}$	[mg kg wwt <sup>-1</sup> ]
	Local PEC in pore water of agricultural soil	$2.91 \times 10^{-3}$	[mg l <sup>-1</sup> ]
	Local PEC in pore water of grassland	$1.16 \times 10^{-3}$	[mg l <sup>-1</sup> ]
	Local PEC in groundwater under agricultural soil	$2.91 \times 10^{-3}$	[mg l <sup>-1</sup> ]
Exposure concentration in sewage treatment plants (STP)	No measured data are available for the concentration of citric acid in sewage treatment plants (STP). The concentration of the citrate has been estimated using EUSES 2.1.1. The EUSES model uses the Simple Treat sewage treatment model to predict the fate of a substance in the STP, based on the physicochemical and biodegradation properties. For citric acid, SimpleTreat predicts the following: 12.6 % to water: 0.112 % to air: 0.0154 % to sludge: 87.3 % degraded. Sludge from WWTPs may be spread on agricultural soil.		



# Citric acid

Revision date: 02 Dec 2013

Substance / User identity		
	Registration number(s)	01-2119457026-42-xxxx
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	11. Use in paints and coatings
	Processes and activities covered by the exposure scenario	SU3, SU21, SU22, SU17, SU18, SU19 PROC 7, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 19, PROC 21, PROC 24
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Worker All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	Solid.
	Concentration of substance in preparation or article	
	Other relevant operational conditions of use	N/A
Formulation of exposure scenario:		
2.1	Formulation of exposure scenario	<p>A paint factory formulating 10000 tpa of formulated paint could need around 10000 x 0.001 = 10 tpa of citric acid. Paint formulation is a widespread activity and this estimate is consistent with a total market size of 300 tpa.</p> <p>It is taken that the regional tonnage is 40 tpa.</p> <p>Assuming a worst case of 2% handling loss this is a local release of 200 kg per year. Such a wastage rate is less than for scenarios considered earlier and there is no need to calculate local exposures. The releases will be added as regional and continental losses to waste water:</p> <p>Regional = <math>200 \times (40/10) / 365 = 2.2 \text{ kg/d}</math></p> <p>Continental <math>2.2 \times (260/40) = 14.3 \text{ kg/d}</math></p>
	Use	<p>The coating process used by both professionals and consumers is typically by brush or roller application. For releases to waste water during consumer use, the OECD Emission Scenario Document for coatings assumes that an estimated 1% of the volatile fraction of the coating will be lost as brush residues and then end up in the sewer. The same fraction (1%) of the volatile fraction is assumed to be lost during professional use, but this is properly disposed and does not end up in the sewer [OECD, 2007].</p> <p>Therefore the amount of citric acid in the application passing to waste is estimated to be widely dispersed:</p> <p>Regional wastewater:</p> <p><math>0.1 \times 300 \text{ tpa} \times 1000 \text{ kg/t} \times 0.01 / 365 = 0.82 \text{ kg/d}</math></p> <p>Continental wastewater:</p> <p><math>0.9 \times 300 \text{ tpa} \times 1000 \text{ kg/t} \times 0.01 / 365 = 7.40 \text{ kg/d}</math></p>

## Citric acid

Revision date: 02 Dec 2013

		<p>Therefore, for simplicity, for this application area, the totals are:</p> <p>Regional wastewater:</p> <p>+ 0.82 = 3.0 kg/d</p> <p>Continental wastewater:</p> <p>14.3 + 7.4 = 21.7 kg/d</p> <p>For human health worker exposure at paint production sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.</p>
--	--	--



# Citric acid

Revision date: 02 Dec 2013

Substance / User identity		
	Registration number(s)	01-2119520510-57-0002
	Substance identity	CAS# 7775-14-6 ,EC#231-890-0
1	Short title of the exposure scenario	12、 Use in photography
	Processes and activities covered by the exposure scenario	SU20,SU21,SU22 PROC5, PROC 13
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Worker All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	Solid.
	Concentration of substance in preparation or article	
	Other relevant operational conditions of use	N/A
Formulation of exposure scenario:		
2.1	Exposure scenario	<p>Citric acid is one of a range of complexing agents used in photography to control the effects of calcium and magnesium hardness, and to keep iron soluble in solution as part of redox processes.</p> <p>Due to the rapid growth of digital photography, use of chemicals in film processing is now limited almost entirely to a small number of professional providers. The chemicals used are collected by photochemical companies in order to recover silver and disposal to drain does not take place.</p> <p>Citrate may also be used as a stop bath in professional or consumer settings as part of the process for the manual development of photographic film. Releases to the environment from this application are insignificant compared to those from considered in other exposure scenarios (cleaning products for example).</p> <p>Therefore this scenario need not be considered further in respect of the environment.</p>
	human health	<p>For human health, the processes applied during both professional and consumer uses are:</p> <p>PROC 9 Transfer of substance or preparation into small containers (dedicated filling line, including weighing)</p> <p>PROC 5 Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)</p> <p>PROC 13 Treatment of articles by dipping and pouring</p>

# Citric acid

Revision date: 02 Dec 2013

Substance / User identity	
	Registration number(s) 01-2119457026-42-xxxx
	Substance identity CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario 13. Use in paints and coatings
	Processes and activities covered by the exposure scenario SU3 PROC 1, PROC 2, PROC 4, PROC 8a
2	Operational conditions and risk management measures
	Duration an frequency of use
	Worker All applicable PROCs >4h
	Physical form of substance: under conditions of use it is used as a liquid. Solid.
	Concentration of substance in preparation or article
	relevant operational conditions of use Following the REACH descriptor system [ECHA, 2009] the following sector of use is covered by this scenario: SU3 Industrial uses  The relevant product category is PC21 Laboratory chemicals  Citric acid may be used at low levels within laboratories. Exposures will take place but under highly controlled conditions. Therefore this scenario need not be considered further for human health or the environment.

# Citric acid

Revision date: 02 Dec 2013

Substance / User identity		
	Registration number(s)	01-2119457026-42-xxxx
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	14. Use in water treatment
	Processes and activities covered by the exposure scenario	SU3, SU14, SU15, SU16, SU17, PROC 1, PROC 2, PROC 3, PROC 4, PROC 7, PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 13, PROC 17, PROC 18, PROC 20, PROC 23, PROC xyz <sup>1</sup>
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Worker All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	Solid.
	Concentration of substance in preparation or article	
	relevant operational conditions of use	This scenario covers use in smaller-scale circulating water treatment in industrial settings, which typically use high substance concentration at low discharges and would usually have a waste water treatment plant (WWTP) in place. The degradability of citric acid in power station cooling systems makes in not suitable for such purposes.
Formulation of exposure scenario:		
2.1	Industrial cooling systems	<p>Industrial cooling systems can be categorized by their design and by using water as coolants. The exchange of heat between process medium and coolant is enhanced by heat exchangers. From the heat exchangers the coolant transports the heat into the environment.</p> <p>Usage of water treatments containing citrates would be continuous for the correct functioning of the cooling water system. Re-loading may be needed more or less frequently, for open and closed cooling water systems respectively, to refresh the system.</p> <p>The worst-case for the local environment is to assume treatment of a large industrial plant, open cooling system, which requires the use of large volumes of a high concentration product on a continuous basis and involves the direct release of blow down effluent to the river or receiving water.</p>
	In open recirculating systems	<p>In open recirculating systems, alkaline conditions (pH of 8-9), in combination with organic complexing agents are effective against corrosion and scaling. Most currently used corrosion programmes are based on phosphates, and zinc is added if water conditions require this.</p> <p>Typical concentrations of scale control agents (polyphosphates, phosphonates, polyacrylates, copolymers and ter-polymers) range from 2 to 20 mg/l, as active compound. Hardness stabilisers prevent the formation of crystals and are used in recirculating systems, but rarely or never in once-through systems. Citrates may be used to enhance the performance of the other additives.</p> <p>In most downstream uses treatment chemicals are applied in water-based processes. The final concentration in the water used in scale inhibition is typically from less than 1 to 10 ppm. Depending on the exact nature of the process, the complexing agents may remain present in the aqueous effluent and the discharge streams. These streams will be treated on the user's site, discharged to sewer</p>

## Citric acid

Revision date: 02 Dec 2013

	<p>systems or discharged to waterways (wide dispersive use).</p> <p>Given the low volatility and the high water solubility of the substances, direct releases to air and soil can be considered negligible.</p>
Wastewater	<p>In the UK, the capacity of 50% of installed base cooling towers is in the range of 22.7 m<sup>3</sup> and 227 m<sup>3</sup> (OECD, 2004). The water circulation rate of a typical open cooling system (with capacity of 100 m<sup>3</sup>), for an industrial plant, is assumed to be 350 m<sup>3</sup>/h (3.5 times the capacity). The blowdown of open cooling systems is related to the rate of evaporation (1% of the circulation rate) and the concentration cycle, which is the ratio (typically 3) of the maximum concentration of dissolved solids in the recirculating water to the concentration in the make up water (OECD, 2004).</p> <p>For the purpose of this calculation, a scaling inhibitor product with an active content of citrate at 25% is assumed. Therefore, for a blowdown of 1.75 m<sup>3</sup>/h from an open cooling system; the estimated release of citrates to water is</p> $0.25 \times 20 \text{ mg/l} \times 1.75 \text{ m}^3/\text{h} \times 1000 \text{ l/m}^3 \times 24 \text{ h/d} \times 10^{-6} \text{ kg/mg}$ $= 0.44 \text{ kg/day.}$ <p>This is lower than ES considered above and there is therefore no need to develop the scenario further.</p> <p>In the nature of the use it must be assumed that all the citric acid used in water treatment could pass to waste water. Therefore:</p> <p>Regional wastewater:</p> $\times 1000 \text{ tpa} \times 1000 \text{ kg/t} / 365 = 274 \text{ kg/d}$ <p>Continental wastewater:</p> $0.9 \times 1000 \text{ tpa} \times 1000 \text{ kg/t} \times / 365 = 2470 \text{ kg/d}$
human health	<p>For human health worker exposure at industrial sites will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.</p>

# Citric acid

Revision date: 02 Dec 2013

Substance / User identity		
	Registration number(s) 01-2119457026-42-xxxx	
	Substance identity CAS#77-92-9; EC#201-069-1	
1	Short title of the exposure scenario 15. Use in metal surface treatment	
	Processes and activities covered by the exposure scenario SU3, SU14, SU15, SU16, SU17, SU21, SU22 PROC 2, PROC 3, PROC 4, PROC 7, PROC 8a, PROC 8b, PROC 9, PROC 10, PROC 13, PROC 17, PROC 18, PROC 23	
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Worker All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	Solid.
	Concentration of substance in preparation or article	
	relevant operational conditions of use	Citric acid may be used as a complexing agent during metal surface treatment operations. This includes cleaning, brightening and passivation of fabricated stainless steel components, and other metal components, cleaning of circuit boards prior to soldering, and metal cleaning or chemical polishing for the surface treatment of aluminium, copper and other metals. The following applications should be taken as representative rather than the sole example of where and why citric acid or citrates may be used in the treatment of metal surfaces. Some industries using citric acid include fasteners, medical devices, semi-conductors, automotive and aerospace.
Passivation	Citric acid may be used in stainless steel passivation to remove iron from the surface of the stainless steel and prevent later corrosion. After thorough cleaning, the stainless steel part is immersed in a passivating acid bath. Any one of three approaches can be used: nitric acid passivation, nitric acid with sodium dichromate passivation and citric acid passivation. Which approach to use depends on the grade of stainless steel and prescribed acceptance criteria. When citric acid passivation is used, typical solutions range from 4 to 10% citric acid by weight.	
Electroless plating	Plating describes the coating of surfaces with metals, either through an electrolysis or electroless plating processes. Electroless plating is also known as 'autocatalytic' plating; deposition of the metal starts on metal nuclei such as palladium and continues autocatalytically. Electroless plating is favoured over electrolysis for most component production (EA 2009).  There are usually three stages in the electroless plating process: de-smearing, activation and electroless copper plating. The plating solution has a copper content of 2 – 5 g/l, with sodium hydroxide (15 – 20 g/l), complexing agents (10 – 15 g/l) or tartrates (5 – 10 g/l) and reducing agents, such as formaldehyde (3 – 5 g/l). The process solution lifetime is limited by the build-up of reaction products and is proportional to the rate of throughput of components (EA 2009). Citrate may be used as a complexing agent.  Electroless plating involves the large-scale use of water in both providing the medium for the process itself and for the subsequent rinsing and washing of components. There is a degree of recycling of rinse water through use to top-up the plating tanks, but there is ultimately loss through carry-over on components. Spent fluids can only be topped up a limited number of times before the media needs replacing. Water-soluble waste is discharged in waste water for basic on-site	

## Citric acid

Revision date: 02 Dec 2013

		treatment (settling and pH adjustment) before discharge to municipal treatment works, controlled by local discharge consent agreements (EA 2009).
	Exposure scenario:	
2.1	Environment exposure	The use of citrate in metal-surface treatment is estimated as approx. 1000 tpa. Therefore, environmental releases are not dissimilar to those discussed in the cleaning scenario (ES5) but on a much smaller scale. Therefore, it is not considered necessary to further assess environmental exposure.
	human health	For workers, exposures are not expected to be greater than those discussed in other industrial use scenarios. The basic risk management measures discussed for these scenarios are considered sufficient to ensure safe use. Human health exposure is not discussed further.



# Citric acid

Revision date: 02 Dec 2013

Substance / User identity		
	Registration number(s)	01-2119457026-42-xxxx
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	16. Use in agriculture
	Processes and activities covered by the exposure scenario	SU1, SU3, SU21, SU22 PROC 3, PROC 5, PROC 8a, PROC 8b, PROC 10, PROC 11, PROC 14, PROC 15, PROC 19
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Worker All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	Solid.
	Concentration of substance in preparation or article	
	relevant operational conditions of use	This scenario covers use in smaller-scale circulating water treatment in industrial settings, which typically use high substance concentration at low discharges and would usually have a waste water treatment plant (WWTP) in place. The degradability of citric acid in power station cooling systems makes in not suitable for such purposes.
Formulation of exposure scenario:		
	Wastewater	The amount of citric acid believed to be used in this application is at most 1500 tpa. The use per site is unknown, but this should be considered as a widely dispersed use. In the worst case a release of the entire tonnage to the region could be included, i.e. 1500 tpa. Of this, part will be released to agricultural soil (90%) and part to waste water (10%).  A regional release of $150 \times 1000/365 = 411$ kg/d to waste water will be added to the model, and 3699 kg/d to soil will be included.
	human health	For human health worker exposure will be to aqueous formulations for which no hazard has been identified. In addition, relevant exposures have been calculated for life cycle stages with higher exposures. Therefore no attempt at quantification will be made nor is needed.



# Citric acid

Revision date: 02 Dec 2013

Substance / User identity		
	Registration number(s)	01-2119457026-42-xxxx
	Substance identity	CAS#77-92-9; EC#201-069-1
1	Short title of the exposure scenario	17. Use in medical devices
	Processes and activities covered by the exposure scenario	SU3, SU20, SU22 PROC 1
2	Operational conditions and risk management measures	
	Duration an frequency of use	
	Worker All applicable PROCs	>4h
	Physical form of substance: under conditions of use it is used as a liquid.	Solid.
	Concentration of substance in preparation or article	
	relevant operational conditions of use	Citrates may be used in medical devices, for example, citrate is added to human blood to prevent coagulation. The whole blood collection process is a closed process as sterility must be maintained. Procedures are carried out by trained personnel in a controlled environment. Therefore, exposures from this use are expected to be minimal and the scenario is not considered further for human health or the environment.



# Citric acid

Revision date: 02 Dec 2013

Substance / User identity						
	Registration number(s)		01-2119457026-42-xxxx			
	Substance identity		CAS#77-92-9; EC#201-069-1			
1	Short title of the exposure scenario		18. Regional exposure concentrations			
	Processes and activities covered by the exposure scenario		N/A			
2	Regional exposure concentrations					
		<b>Predicted regional Exposure Concentrations</b>		<b>Measured regional exposure concentrations</b>		<b>Explanation / source of measured data</b>
		<b>value</b>	<b>unit</b>	<b>value</b>	<b>unit</b>	
	Freshwater	$1.52 \times 10^{-2}$	mg/l	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1
	Marine water	$1.41^{-3}$	mg/l	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1
	Freshwater sediments	$3.32 \times 10^{-1}$	mg/kg d.w.	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1
	Marine sediments	$2.60 \times 10^{-2}$	mg/l	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1
	Agricultural soil	$3.19 \times 10^{-3}$	mg/kg wwt	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1
	Grassland	$7.47 \times 10^{-12}$	mg/kg wwt	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1
	Air	$1.24 \times 10^{-19}$	(mg/m <sup>3</sup> )	No data		The value represents the sum of the regional PECs calculated by EUSES 2.1.1